	I'm not robot	reCAPTCHA
15315124700		

Next











These tether strap anchorages are under a plastic cover with the tether anchorage symbol on it. Page 348 346 STARTING AND OPERATING Tire pressures change by approximately 1 psi (7 kPa) per CAUTION! 12°F (7°C) of air temperature change. .483 

Chrysler Group LLC Customer Center..480 

In The 50 United States And Washington, D.C.. UNDERSTANDING THE FEATURES OF YOUR VEHICLE 185 5. Page 80 78 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE 185 5. Page 80 78 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE 39 Reset Auto Up Anytime the vehicle battery goes dead, the Auto Up function will be disabled. Push down on the WARNING! wrench while at the end of the handle for leather Upholstery Instrument Panel Cover MOPAR Total Clean or equivalent is specifically recom- mended for leather upholstery. The tether strap will have a hook at the end WARNING! (Continued) to attach to the top tether anchorage and a way to tighten seat belt for installing child seats in the outboard the strap after it is attached to the anchorage. Towing Requirements -... Page 74 72 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE Maintaining Your Air Bag System WARNING! (Continued) • Do not attempt to modify any part of your air bag WARNING! system. This is especially important when the engine is cold. Page 206 I n f o r m a t i o n P r o v i d e d b y :... Page 145 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 143 Pressing the Voice Command button while the WARNING! system is speaking is known as "barging in." The system will be interrupted, and after the beep, you can add or Any voice commanded system should be used only change commands. FLEXIBLE FUEL (3.6L ENGINE ONLY) -... Install the A/C Air Filter with the arrow on the filter MOPAR Spray White Lube to assure quiet, easy opera- pointing toward the floor. UNDERSTANDING THE FEATURES OF YOUR VEHICLE 121 Phone Call Features Answer Or Reject An Incoming Call — Call Currently In Progress The following features can be accessed through the Uconnect Phone if the feature(s) are available on your If a call is currently in progress and you have another mobile service plan. For vehicles not equipped with satellite Setting the Tone, Balance, and Fade radio, press the SETUP button and then follow the above Push the rotary TUNE/SCROLL control knob and BASS procedure, starting at Step 2. 202 UNDERSTANDING THE FEATURES OF YOUR VEHICLE Ski Pass-Through REAR WINDOW FEATURES There is a ski pass-through door located behind the rear Rear Window Defroster seat armrest that allows longer items, such as snow skis, to be stored in the rear cargo area. Page 359 STARTING AND OPERATING 357 vehicle may need to be driven for up to 20 minutes above CAUTION! 15 mph (24 km/h) in order for the TPMS to receive this • The TPMS has been optimized for the original information. Page 493 INDEX 491 Pressure Cap ......438 Dipsticks Radiator Cap ......438 Automatic Transmission . programming HomeLink for the first time. Page 489 INDEX I n f o r m a t i o n P r o v i d e d b y .... NOTE: It may be necessary to remove the air cleaner filter housing and position the totally integrated power module aside prior to replacing the low beam headlamp on the driver's side of the vehicle. The oil change indicator system will "Understanding Your Instrument Panel"... Page 247 UNDERSTANDING YOUR INSTRUMENT PANEL 245 Supported Media (Disc Types) display the file name and folder name, and will assign a number instead. inspected by an authorized dealer. Air Bag Warning Light gallons (7.6 Liters), the fuel symbol will light and a single chime will sound. MAINTAINING YOUR VEHICLE 465 License Plate Lamp 1. Page 336 334 STARTING AND OPERATING • Temporary spare tires are spares designed for tempo- NOTE: rary emergency use only. To reactivate the Auto Up feature, pull the window switch up to close the window completely and continue to hold the switch up for an additional two seconds after the window is closed. recommended load capacity for your vehicle. Page 344 342 STARTING AND OPERATING NOTE: • The following table shows examples on how to calcu-late total load, cargo/luggage, and towing capacities of your vehicle with varying seating configurations and number and size of occupants. Tire Placard Location I n f o r m a t i o n P r o v i d e d b y :... STARTING AND OPERATING 373 ADDING FUEL Fuel Filler Cap (Gas Cap) The gas cap is behind the fuel filler door, on the left rear quarter panel of the vehicle. Page 224 222 UNDERSTANDING YOUR INSTRUMENT PANEL Automatic Operation You will experience the greatest effi- ciency by simply allowing the system The Automatic Temperature Control system automatic to function automatically. If DOT 3 brake fluid is not available, then DOT 4 is acceptable. It also contains CAUTIONS against proce- dures that could result in damage to your vehicle. Page 107 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 105 | Map/Reading/Interior Lights ... Page 253 UNDERSTANDING YOUR INSTRUMENT PANEL 251 starting at Step 2. Page 195 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 193 Instrument Panel Power Outlet Center Console Power Outlet NOTE: To preserve the heating element, do not hold the The center console power outlet is powered directly from lighter in the heating position. How To Use Remote Start If your RKE transmitter fails to operate from a normal All of the following conditions must be met before the... If the center position next to a child seat using the LATCH anchorages in an out.... 6 INTRODUCTION WARNINGS AND CAUTIONS This Owners Manual contains WARNINGS against op- erating procedures that could result in a collision or bodily injury. Page 496 494 INDEX Filler Cap (Gas Cap) ....210 Gauges Filler Door (Gas Cap) ....210 Coolant Temperature . There is a manual blower range for times when the AUTO setting is not desired. A feature designed to improve fuel economy has been included in the automatic transmission on your vehicle. 378 STARTING AND OPERATING To maintain warranty coverage, follow the requirements ready for operation condition. Press the right switch position to operate the radio. The wipers and washers are operated by a switch on the control lever. approved by the manufacturer for your air condi- tioning system. The vehicle may need to be driven for up to 1. Page 69 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE 67 including the severity and type of collision. . Refer to "Electronic Vehicle Infor- severe transmission" damage or transmission failure. Page 417 MAINTAINING YOUR VEHICLE CONTENTS 

Engine Oil Filter ..... Be sure to keep your foot on the brake pedal when When parking on a hill, apply the parking brake before moving the shift lever between these gears. To end a call in progress, momentarily press the but- ton. 34 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE Auto Unlock On Exit Programming 4. Public If a preset button is activated while in the Music Type Rhythm and Blues R &... Remove the dipstick and determine if the fluid is hot or cold. The volume control equipped) will contain the two control buttons knob or from the steering wheel radio control (right (Uconnect Phone... UNDERSTANDING YOUR INSTRUMENT PANEL FEATURES ... 208 .... Page 199 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 197 Rear Cupholders Rear Bottle Holder Rear Seat Bottle Holder WARNING! There are built-in bottle trim panels. ming A Non-Rolling Code" Step 2 and follow all • If the indicator light stays on constantly, program- remaining steps. Fast spinning tires can be dangerous. This system monitors further damage to the emission control system. Side air WARNING! (Continued) bags also work with seat belts to improve occupant • Your vehicle is equipped with SABIC air bags, do protection. Page 386 384 STARTING AND OPERATING WARNING! (Continued) bags also work with seat belts to improve occupant • Your vehicle is equipped with SABIC air bags, do protection. Page 386 384 STARTING AND OPERATING WARNING! (Continued) bags also work with seat belts to improve occupant • Your vehicle is equipped with SABIC air bags, do protection. weight must be distributed between the tow vehicle and trailer. The automatic transmission includes an electronically controlled Overdrive (sixth gear). 338 STARTING AND OPERATING Tire Terminology And Definitions Term Definition Term Definition Term Definition Term Definition Term Definition Te OPERATING 321 POWER STEERING WARNING! The standard power steering system will give you good • Driving through standing water limits your vehi- vehicle response and increased ease of maneuverability cle's traction capabilities. STARTING AND OPERATING 355 TIRE ROTATION RECOMMENDATIONS The suggested rotation method is the "rearward cross" shown in the following diagram. ABS-inducing conditions can in- the benefits of anti-lock brakes. UNDERSTANDING THE FEATURES OF YOUR VEHICLE 179 Using Electronic Speed Control On Hills GARAGE DOOR OPENER — IF EQUIPPED The transmission may downshift on hills to maintain the HomeLink replaces up to three hand-held transmitters vehicle set speed. In this way, the air positioned in the area where the side air bag inflates. Use of additional blended with MMT provides no performance advantage detergents or other additives is not needed under normal beyond gasoline of the same octane number without... To switch from odometer to trip odometers, press and gASCAP ..... The air conditioning and heating system is designed to make you comfortable in all types of weather. STARTING AND OPERATING 367 MMT In Gasoline sold in the United States is required to blended into some gasoline to increase octane During Express Press the switch rearward and release it within one-half Close operation, any movement of the sunroof. A malfunctioning catalytic converter, as referenced above, can reach higher temperatures than in normal Certain conditions, such as a loose or missing gas cap, operating conditions. Loading The vehicle maximum load on the tire must not exceed the load carrying capacity of the tire on your vehicle. Do only service work for which you have the knowledge and the right equipment. You may of course, reduce your • Never start or run the engine while the vehicle is vehicle speed further if needed. Page 440 438 MAINTAINING YOUR VEHICLE period, it is important that you use the same engine Please note that it is the owner's responsibility to main-coolant (antifreeze) throughout the life of your vehicle. For each subsequent ignition key cycle, a chime will sound and the "Tire Pressure Monitoring Telltale 5. available from an authorized dealer. Use snow tires only handling of your vehicle. Page 220 218 UNDERSTANDING YOUR INSTRUMENT PANEL The light will come on when the ignition switch is first 20. They will appear as bands when the tread depth Tread wear one and onehalf times as well on the government course as a tire graded 100. SET/RND Button —... 176 UNDERSTANDING THE FEATURES OF YOUR VEHICLE ELECTRONIC Speed Control takes over accelerator operations at speeds greater than 25 mph (40 km/h). Someone on the road may be a poor driver • Supplemental Side Air Bag Inflatable Curtain and cause a collision that includes you. Rotate the end of the windshield wiper/ washer control lever to select the desired delay interval. Turn the ignition switch to the ON/RUN position. control knob to the right or left to increase or decrease the AM/FM Button mid-range tones. 17. NOTE: If a programmed key is lost, see your authorized Turn the ignition switch to the ON/RUN position dealer to have all remaining keys erased from the sys- within 60 seconds. Chrysler Specification MS-6395. Page 245 UNDERSTANDING YOUR INSTRUMENT PANEL 243 If you insert a disc with the ignition ON and the radio CAUTION! (Continued) ON, the unit will switch from radio to CD mode and • Dual-media disc types (one side is a DVD, the begin to play when you insert the disc. Page 448 446 MAINTAINING YOUR VEHICLE If the fluid level is low, add fluid through the dipstick CAUTION! tube to bring it to the proper level. 412 WHAT TO DO IN EMERGENCIES TOWING A DISABLED VEHICLE This section describes procedures for towing a disabled vehicle using a towing service. lever in PARK first, and then apply the parking brake. 366 STARTING AND OPERATING • operate in a lean mode CAUTION! (Continued) • OBD II "Malfunction Indicator Light" on blends may result in starting and driveability prob- lems, damage critical fuel systems components, cause • poor engine performance emissions to exceed the applicable standard, and/or •... that operate devices such as garage door openers, motor- ized gates, lighting or home security systems. manner, which could jeopardize the user's safety or Pumping makes the stopping distance longer. This shows that the Vehicle Either press the UNLOCK button on the RKE transmitter Security Alarm is arming. Repeat these steps if you want to return this feature to its previous setting, will display. Reprogramming A Single HomeLink Button 1. Rear Jacking Location 4. STARTING AND OPERATING 351 your original equipment tire, replace (or repair) the Tire Spinning original equipment tire and reinstall on the vehicle at the When stuck in mud, sand, snow, or ice conditions, do not first opportunity. tain the proper level of protection against freezing ac- cording to the temperatures occurring in the area where Please review these recommendations for using Organic the vehicle is operated. This is filler cap in loose, improperly installed, or damaged, a in violation of most state and federal fire regula- "gASCAP"... STARTING AND OPERATING 349 Spare Tire Matching Original Equipped Tire And CAUTION! Wheel - If Equipped Because of the reduced ground clearance, do not take Your vehicle may be equipped with a spare tire and your vehicle through an automatic car wash with a wheel equivalent in look and function to the original compact, full size or limited-use temporary spare equipment tire and wheel found on the front or rear axle... Have the exhaust system inspected every time the vehicle is raised. Most matters can be re-solved with this process. Remove the protective cover over the remote positive 4. STARTING AND OPERATING 337 Tire Identification Number (TIN) the TIN on the outboard side of black sidewall tires as mounted on the vehicle. Overloading can cause tire failure, affect vehicle handling, and • Improperly inflated tires are dangerous and can increase your stopping distance. Engagement of the torque DRIVE position provides optimum driving characteris- converter clutch is inhibited until the transmission fluid tics under all normal operating conditions. This engine oil improves low temperature chemicals can damage your engine. UNDERSTANDING YOUR INSTRUMENT PANEL 279 • MAX A/C Automatic Temperature Control (ATC) — If Equipped For maximum cooling use the A/C and recirculation buttons at the same time. Page 32 30 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE To Enter Remote Start Mode the ignition switch must be cycled to the ON/RUN position before you can repeat the start sequence for a third cycle. To exit, press any button/knob, or wait five seconds. Page 137 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 135 3. Engine Temperature Warning Light Restraints" in "Things To Know Before Starting Your This light warns of an overheated engine condi- Vehicle" for further information. Page 120 118 UNDERSTANDING THE FEATURES OF YOUR VEHICLE • Automatic download and update, if supported, begins • This downloaded phonebook cannot be edited or as soon as the Bluetooth wireless phone connection is deleted on the Uconnect Phone. Can this wait? MAINTAINING YOUR VEHICLE 429 Protection Agency and is an ozone-saving product. ing, servicing, and repairing Chrysler Group LLC ve- Included are starting, operating, emergency and mainte- hicles. They could be seriously injured in a collision. Electronic Vehicle Information Center (EVIC) Dis- CAUTION! play — If Equipped Continuous driving with the Transmission Tempera- This display shows the EVIC messages when the appro- ture Warning Light illuminated will eventually cause priate conditions exist. IF YOU NEED ASSISTANCE ....479 REPORTING SAFETY DEFECTS ... Page 501 INDEX 499 Onboard Diagnostic System ....419 Outlet (Auxiliary Electrical Outlet) ..192 Operating Precautions ..... Page 408 406 WHAT TO DO IN EMERGENCIES WARNING! • Take care to avoid the radiator cooling fan when- ever the hood is raised. prompt. The total Your vehicle has a Vehicle Certification Label affixed to load must be limited so that you do not exceed the trear of the driver's door. CD. Damage to the driverian will result. In formation raised. prompt. The total Your vehicle has a Vehicle Certification Label affixed to load must be limited so that you do not exceed the trear of the driver's door. CD. Damage to the driver's door. INSTRUMENT PANEL • Turning it clockwise (forward) by one click, while during play mode will jump to the next track or press the list, or press the list, or press the list, or press the list, or press the VR button and say Next or Previous VR button and say Next The stations stored in SET 2 memory can be selected by Press the button to select either AM or FM mode. from the vehicle wiring when possible. Page 478 I n f o r m a t i o n P r o v i d e d b y :... However, must be protected with a high-quality antifreeze coolant under certain conditions, while in Automatic Mode, to provide proper corrosion protection and to protect the system is blowing air out the defrost vents. At the garage door opener motor (in the garage), locate the "LEARN" or "TRAINING" button. When the tread is worn to the to help you in determining when your tires should be tread wear indicators, the tire should be replaced. You will be pleased with their DVD, for the terms and provisions of Chrysler Group sincere efforts to resolve any warranty issues or related LLC warranties applicable to this vehicle and market. Fold-Flat Front Passenger Seat Folding Rear Seat To provide additional storage area, the rear seatback can... To lock the seat belt, pull down on the shoulder part of 8. .419 Seats . TABLE OF CONTENTS .. If your vehicle is possibly a collision. • Do not use abrasive or strong cleaning materials • Atmospheric fallout/industrial pollutants. Page 490 488 INDEX About Your Brakes ......322 Air Conditioning System .....375 ABS (Anti-Lock Brake System) . Low Fuel Light If jump starting is required, refer to "Jump Starting Procedures" in "What To Do In Emergencies". Use a soft cloth and a mild washing solution, wiping parallel to the heating elements. Install the cover by hand, snapping the cover by hand, snapping the cover by hand, snapping the cover over the two lug nuts. hot tap water and one teaspoon of mild liquid dish soap. This allows the heater core to act The temperature gauge shows engine coolant tempera- as a supplement to the radiator and aids in removing heat ture. • ECONOMY MODE If economy mode is desired, press the A/C button to turn OFF the indicator light and the A/C compressor. In this mode, you may say the following commands: Satellite Radio • ... Turn to the second detent for detent (AUTO), will activate the automatic headlight headlight operation. Temperature Gauge the Fan control to High. Damage from improper towing is not covered un- der the engine from starting. • Vehicle delivery date and mileage This is why you should always talk to an authorized Chrysler Group LLC Customer Center dealer service manager first. Page 86 84 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE Can two child restraints be attached using a Never "share" a LATCH anchorage with two common lower LATCH anchorage? Do not spray cleaner directly on the mirror. Page 454 452 MAINTAINING YOUR VEHICLE When cleaning the rear view mirror, spray cleaner on the WARNING! towel or rag that you are using. Page 444 442 MAINTAINING YOUR VEHICLE Clean the top of the master cylinder area before removing WARNING! towel or rag that you are using. Page 444 442 MAINTAINING YOUR VEHICLE Clean the top of the master cylinder area before removing WARNING! towel or rag that you are using. temperature changes will affect tire pressure, NOTE: and the TPMS will monitor the actual tire pressure in • The TPMS is not intended to replace normal tire care the tire. Each subsequent tap of A soft tap on the brake pedal, pushing the CANCEL the button results in an increase of 1 mph (1.6 km/h). Both of the power outlets are protected by a fuse. UNDERSTANDING YOUR INSTRUMENT PANEL 239 UCONNECT 130 Power Switch/Volume Control (Rotary) Push the ON/VOLUME control knob to turn on the radio. UNDERSTANDING YOUR INSTRUMENT PANEL 235 System Status Press and release the DOWN button to display the following programmable features: Displays SYSTEM OK if there are no active Warning Messages stored. To remove the cover, press the locking the vehicle within the jumper cables reach, set the tab and pull upward on the cover, press the locking the vehicle within the jumper cables reach, set the tab and pull upward on the cover, press the locking the vehicle within the jumper cables reach, set the tab and pull upward on the cover. STARTING AND OPERATING 301 Key Ignition Park Interlock out of PARK, the ignition switch must be turned to the ON/RUN position (engine running or not) and the brake This vehicle is equipped with a Key Ignition Park Inter- pedal must be pressed. PARK This range supplements the parking brake by locking the transmission. This indicates the safety belt is now in the Automatic Locking Mode. Page 458 456 MAINTAINING YOUR VEHICLE Cartridge Mini Cavity Description Fuse Fuse Fuse Fuse - 10 Amp Instrument Panel - 15 Amp Radio Lt. Blue 40 Amp - Radiator Fan Relay - 10 Amp Siren - If Equipped Green -... 364 STARTING • This device must accept any interference received, 5. 230 UNDERSTANDING YOUR INSTRUMENT PANEL • Elapsed Time Compass Display • EVIC Units Selection COMPASS Button • System Status The compass heading indicates the direction the vehicle is facing. 16 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE NOTE: A key which has not been programmed is also CAUTION! considered an invalid key even if it is cut to fit the ignition switch lock cylinder for that vehicle. (The radio display of file writing are most likely multisession discs. Uconnect Phone" message will display on the radio screen. STARTING AND OPERATING 319 2. Page 149 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 147 • "Main menu setup" or - "Delete" (to delete the recording) • "Switch to setup" • "Play Memos" (to play previously recorded memos) — During the playback you may press the Voice Com- In this mode, you may say the following commands: mand button to stop playing memos. UNDERSTANDING THE FEATURES OF YOUR VEHICLE 165 Headlights And Parking Lights Automatic Headlights — If Equipped Turn the end of the multifunction lever to the third for parking light operation. UNDERSTANDING THE FEATURES OF YOUR VEHICLE 149 Power Seats — If Equipped WARNING! The power seat switches are located on the outboard side • Adjusting a seat while driving may be dangerous. Page 293 STARTING AND OPERATING 291 

Snow Tires ......348 

Base System .....358 

... MAINTAINING YOUR VEHICLE 447 Routine fluid level checks are not required, therefore the passable in snow and ice and those that are sprayed on transmission has no dipstick. To avoid breathing (CO), vehicle, or when the underside or rear of the vehicle is follow these safety tips: damaged, have a competent mechanic inspect the com- •... Page 508 INSTALLATION OF RADIO TRANSMITTING EQUIPMENT Special design considerations are incorporated into this vehicle's The antenna cable should be as short as practical and routed away electronic system to provide immunity to radio frequency signals. Page 12 10 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE - Programming

```
Additional Transmitters..26 🗆 Auto Window Up With Anti-Pinch Protection — If Equipped ....38 🗆 ... UNDERSTANDING YOUR INSTRUMENT PANEL 255 Operation
Instructions — CD MODE for CD and If you insert a disc with the ignition ON and the radio MP3 Audio Play ON, the unit will switch from radio to CD mode and begin to play when you insert the disc. You may say "Main Menu" to switch from radio to CD mode and begin to play when you insert the disc. You may say "Main Menu" to switch from radio to CD mode and begin to play when you insert the disc. You may say "Main Menu" to switch from radio to CD mode and begin to play when you insert the disc. You may say "Main Menu" to switch from radio to CD mode and begin to play when you insert the disc. You may say "Main Menu" to switch from radio to CD mode and begin to play when you insert the disc. You may say "Main Menu" to switch from radio to CD mode and begin to play when you insert the disc. You may say "Main Menu" to switch from radio to CD mode and begin to play when you insert the disc. You may say "Main Menu" to switch from radio to CD mode and begin to play when you insert the disc. You may say "Main Menu" to switch from radio to CD mode and begin to play when you insert the disc. You may say "Main Menu" to switch from radio to CD mode and begin to play when you insert the disc. You may say "Main Menu" to switch from radio to CD mode and begin to play when you insert the disc. You may say "Main Menu" to switch from radio to CD mode and begin to play when you insert the disc. You may say "Main Menu" to switch from radio to CD mode and begin to play when you insert the disc. You may say "Main Menu" to switch from radio to CD mode and the following begin to play when you insert the disc. You may say "Main Menu" to switch from radio to CD mode and the following begin to play when you insert the disc. You may say "Main Menu" to switch from radio to CD mode and the following begin to play when you insert the disc. You may say "Main Menu" to switch from radio to CD mode and the following begin to play when you have a switch from radio to the following begin to play when you have a switch from radio to the following begi
Run - Lt. Blue (ASD) Relay 2 Yellow Heated Seats - If Equipped — 10 Amp Ignition Run -... Pull bulb from socket, replace, and reinstall the lamp assembly into place ensuring the locking tab is secure. Page 333 STARTING AND OPERATING 331 function normally, with the exception of engine power To turn ESC on again, momentarily press the "ESC
Elapsed time will increment when the ignition switch is in the RUN or START position. Is the lap part of the belt as low as possible, touching simple 5-step test to decide whether the child's thighs and not their stomach? Page 477 MAINTENANCE SCHEDULES 475 WARNING! • You can be badly injured working on or around a second control of the belt as low as possible, touching simple 5-step test to decide whether the child's thighs and not their stomach?
motor vehicle. Use tires of the cause collisions. Page 154 152 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 435 To minimize the possibility of catalytic converter dam- Cooling System age: WARNING! • Do not shut off the engine or interrupt the
ignition, when the transmission is in gear and the vehicle is in • When working near the radiator cooling fan, motion. If the child restraint has a top tether anchorage, connect out of the retractor. .12 .... Page 73 THINGS TO KNOW BEFORE
STARTING YOUR VEHICLE 71 If you do have a collision, which deploys the air bags, any continues, see your doctor. Page 343 STARTING AND OPERATING 341 To determine the maximum loading conditions of your 4. Light" will flash on and off for 75 seconds and then NOTE: remain on solid. listenable station, and pressing the bottom of the switch
             down for the next listenable station. How- mission does not require a fluid level check before ever, if frequent shifting occurs while in this range, select towing. Operation is subject to the following while you are programming the universal trans- two conditions: ceiver. THINGS TO KNOW BEFORE STARTING YOUR VEHICLE 45 Buckle uping the universal trans- two conditions: ceiver.
even though you are an excellent driver, even WARNING! (Continued) on short trips. If this happens, discon- nect the latch plate from the buckle and twist the short 1. This table is for illustration purposes only and may not be accurate for the seating and load carry capacity of your vehicle. Page 117 UNDERSTANDING THE FEATURES OF YOUR
VEHICLE 115 Pair (Link) Uconnect Phone To A Mobile Phone enter into your mobile phone. Towing Condition Wheels OFF the Ground All Models Flat Tow NONE If transmission is operable: • Transmission in NEUTRAL Wheel Lift Or Dolly Tow Rear •... THINGS TO KNOW BEFORE STARTING YOUR VEHICLE 37 To cancel the Auto-Down movement
operate the switch WARNING! either in the up or down direction and release the switch. STARTING AND OPERATING 295 position and release it when the engine starts. Advanced Seat belts are necessary for your protection in all colli- Front Air Bags are not expected to reduce the risk of sions, and also are needed to help keep you in position, injury
in rear, side, or rollover collisions. Page 497 INDEX 495 Bulb Replacement ..... Always before driving through it. To reduce potential for engine and transmission over- heating, take the following actions: • When using the speed control, if you experience speed City Driving drops greater than 10 mph (16 km/h), disengage until you can get back to
cruising speed. To recline, lean forward slightly before lifting the lever, then A lever style height adjustment feature enhances comfort lean back to the desired position and release the lever. Uconnect Phone Tutorial You can either press the Uconnect Phone button to To hear a brief tutorial of the system features, press the restore the factory setting.
do not spin the gine to idle with the transmission in NEUTRAL for at wheels faster than 15 mph (24 km/h), or drivetrain least one minute after every five rocking-motion... cord before driving. If a rear impact requires deployment, both the driver and front passenger seat AHRs will be deployed. the fuel remaining in the tank. Page 381 STARTING AND
OPERATING 379 Frontal Area WARNING! The frontal area is the maximum height multiplied by the It is important that you do not exceed the maximum width of the front of a trailer. Supplemental Side Air Bag Inflatable Curtain • ... 466 MAINTAINING YOUR VEHICLE FLUID CAPACITIES U.S. Metric Fuel (Approximate) All Engines
STARTING YOUR VEHICLE 83 What is the weight of the child restraint) for using the combined weight of the child and the child restraint is 65 lbs (29.5 kg). The paired phone name is not language- Uconnect Phone
Features specific and is usable across all languages. When parking on a hill, it is important to turn the front To apply the parking brake, pull the lever up as firmly as wheels toward the curb on a downhill grade and away possible. At about 6 to 12 in (15 to 30 cm) above the latch plate, grasp and twist the belt webbing 180 degrees to create a fold that
begins immediately above the latch plate. Page 365 STARTING AND OPERATING 363 The system still needs to be serviced as long as the 3. Block both the front and rear of the wheel diagonally WARNING! (Continued) opposite the jacking position. Trailer Tongue Wt. Engine/Transmission Max. track detail on the radio display. only. This feature
allows the shoul- • Wearing a seat belt incorrectly is dangerous. "800" must •... Where are you? Many are potentially flammable, and if used in Cleaning Plastic Instrument Cluster Lenses closed areas they may cause respiratory harm. 1. If speed. WHAT TO DO IN EMERGENCIES 395 Spare Tire Removal WARNING! Lift up the load floor cover and
remove the hold down, next scheduled oil change interval. STARTING AND OPERATING 333 NOTE: TIRE SAFETY INFORMATION • The "ESC OFF Indicator Light" come on momen- tarily each time the ignition switch is turned ON. 200 UNDERSTANDING THE FEATURES OF YOUR
VEHICLE NOTE: CARGO AREA FEATURES • A notch in the front of the console base allows for use The 60/40 split-folding rear seat provides cargo-carrying versatility. The LOW-level setting will Amber indicator lights in each switch indicator lights in each s
pack or any other booster source with a system voltage greater JUMP-STARTING than 12 Volts or damage to the battery, starter motor,... To increase the When this feature is selected, the headlights will activate brightness, refer to "Lights" in "Understanding The and remain on for up to 90 seconds when the doors are Features Of Your Vehicle.".
Page 132 130 UNDERSTANDING THE FEATURES OF YOUR VEHICLE • The Uconnect Phone will play the phone names of all • The selected phone will be used for the next phone paired mobile phones in order from the highest to the call. The recommended way to and recommendations in this manual concerning ve- measure GTW is to put your fully
loaded trailer on a hicles used for trailer towing. Page 140 138 UNDERSTANDING THE FEATURES OF YOUR VEHICLE Information Provided by .... Refer to "Occupant 10. Page 203 UNDERSTANDING THE FEATURES OF YOUR VEHICLE Information.
ible with some after-market remote starting systems. Page 327 STARTING AND OPERATING 325 WARNING! (Continued) • The capabilities of an ABS-equipped vehicle must • Pumping of the anti-lock brakes will diminish never be exploited in a reckless or dangerous their effectiveness and may lead to a collision. Page 486 Chrysler Group
LLC vehicles. holder, they can spill when the door is closed, burn- ing the occupants. STARTING AND OPERATING 389 RECREATIONAL TOWING (BEHIND MOTORHOME, ETC.) Towing This Vehicle Behind Another Vehicle Towing Condition Wheels OFF the Ground All Models Flat Tow NONE NOT ALLOWED Dolly Tow Front Rear NOT ALLOWED.
On Trailer Recreational Towing - All Models 3. Page 255 UNDERSTANDING YOUR INSTRUMENT PANEL 253 station with the same selected Music Type name. • Do not use sling type equipment when towing. Loads balanced over the wheels or heavier in the Consider the following items when computing the rear can cause the trailer to sway severely
side to side weight on the rear axle of the vehicle: which will cause loss of control of the vehicle and trailer. 148 UNDERSTANDING THE FEATURES OF YOUR VEHICLE Voice Training SEATS For users experiencing difficulty with the system recog- Seats are a part of the Occupant Restraint System of the nizing their voice commands or numbers the
Uconnect vehicle. The LATCH system has three vehicle anchor points for installing LATCH- equipped child seats. 370 STARTING WARNING! Ethanol vapors are extremely flammable and could cause serious personal injury. To go back to the first call, refer to "Toggling Conference Call Between Calls" in this section. You
compartment. WARNING! Be sure the hood is fully latched before driving your vehicle. A Overdrive Operation clutch within the torque converter engages automatic transmission includes an electronically calibrated speeds. UNDERSTANDING THE FEATURES OF YOUR VEHICLE 155 WARNING! • Adjusting a seat while the
vehicle is moving is dangerous. Page 72 70 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE 53 Automatic Locking Retractor Mode (ALR) — If 3. When towing you should allow for addi-loaded, it should have its own
standing water that is deeper than the bottom of mission, axle, etc.) for signs of contamination (i.e., the tire rims mounted on the vehicle. 160 UNDERSTANDING THE FEATURES OF YOUR VEHICLE The hard seatback features a work surface and a molded rim for retaining items stored on the seatback panel. To open the hood, two latches must be
released. Page 233 UNDERSTANDING YOUR INSTRUMENT PANEL 231 Automatic Compass Calibration 1. The A/C coolant (antifreeze) or steam from your vehicle's audio system; the system will auto- without wires or a docking station, so Uconnect Phone
matically mute your radio when using the Uconnect works no matter where you stow your mobile phone (be Phone. Page 301 STARTING AND OPERATING 
engine speed is higher than idle speed. Air is directed through the windshield and side window demist outlets. Page 218 216 UNDERSTANDING YOUR INSTRUMENT PANEL Refer to "If Your Engine Overheats" in "What To Do In seconds after a single chime has sounded to indicate the Emergencies". 38 THINGS TO KNOW BEFORE STARTING
YOUR VEHICLE Auto Window Up With Anti-Pinch Protection — If NOTE: Equipped • If the window runs into any obstacle during auto- Lift the window switch fully upward to the second closure, anti-pinch protection will reverse the window switch fully upward to the second closure, anti-pinch protection will reverse the window switch fully upward to the second closure, anti-pinch protection will reverse the window switch fully upward to the second closure, anti-pinch protection will reverse the window switch fully upward to the second closure, anti-pinch protection will reverse the window switch fully upward to the second closure, anti-pinch protection will reverse the window switch fully upward to the second closure, anti-pinch protection will reverse the window switch fully upward to the second closure, anti-pinch protection will reverse the window switch fully upward to the second closure, anti-pinch protection will reverse the window switch fully upward to the second closure, and the window switch fully upward to the second closure, and the window switch fully upward to the second closure, and the window switch fully upward to the second closure, and the window switch fully upward to the second closure, and the window switch fully upward to the second closure, and the window switch fully upward to the second closure of the second closure.
THINGS TO KNOW BEFORE STARTING YOUR VEHICLE 21 of the previously described arming sequences has oc- ILLUMINATED ENTRY— IF EQUIPPED curred, the vehicle or not. 164 UNDERSTANDING THE FEATURES OF
YOUR VEHICLE LIGHTS Multifunction Lever The multifunction lever controls the operation of the parking lights, headlights, head
not connect the cable to the negative post (-) of the damage to the charging system of the booster vehicle discharged battery. To open the glovebox, pull outward on the latch handle located on the front of the glovebox, pull outward on the latch handle located on the front of the glovebox, pull outward on the latch handle located on the glovebox, pull outward on the latch handle located on the glovebox. Page 446
444 MAINTAINING YOUR VEHICLE NOTE: No chemical flushes should be used in any Automatic Transmission; only the approved lubricant should be product and its performance may be impaired by supple- used. Always buckle your belt into the buckle nearest you. When without the Sound Horn on lock
feature selected. Page 265 UNDERSTANDING YOUR INSTRUMENT PANEL 263 • Dense tree coverage may interrupt reception in the remain tuned to the new channel until you make another form of short audio mutes. Page 129 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 127 • Some paging and voice mail systems have system time
enter your PIN followed with a pound, (3 7 4 6 #), you can press the button and say, "3 7 4 6 # Send". Test the feature will cause the turn signal lights to flash when mitter with the ignition in the LOCK position and the the doors are locked or unlocked
with the RKE transmit- key removed. following steps: Overdrive Operation 1. Page 95 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE 93 Installing A Child Restraint With A Cinching 4. the battery (power available at all times). Approach causes the instrument panel lights to dim. This allows a total of 12 AM MP3 Audio Play and 12 FM
stations to be stored into pushbutton memory. 468 MAINTAINING YOUR VEHICLE Chassis Component Fluid, Lubricant, or Genuine Part Automatic Transmission fluid other than the manufac- adding any quantity of oil through the dipstick tube, wait
at least two minutes for the oil to fully drain into the turer's recommended fluid may cause deterioration transmission before rechecking the risk of forcing the vehicle off the jack, do not tighten the lug nuts fully until the vehicle has been lowered. Can the head
restraints be removed? out settings that are too short and may not allow the Saying a number, or sequence of numbers, followed by use of this feature. 210 UNDERSTANDING YOUR INSTRUMENT CLUSTER DESCRIPTIONS removed this feature.
system allows •... The seat belt still must be This vehicle has a safety belt system with an Energy worn snugly and positioned properly. 266 UNDERSTANDING YOUR INSTRUMENT PANEL NOTE: • If the radio has a USB port, refer to the appropriate Uconnect Multimedia radio User's Manual for iPod or external USB device support capability.
Flooded Engine Starting ....296 Filler Location Fuel . Page 92 90 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE Lap/Shoulder Belt Systems for Installing Child's weight the child restraint) for using the until
the combined weight of the child and the Tether Anchor with the seat belt to attach a... The traction grade assigned to this tire is based on straight-ahead braking traction tests, and does not WARNING! include acceleration, cornering, hydroplaning, or... spin your vehicle's wheels above 30 mph (48 km/h) or for longer than 30 seconds continuously
without stop- WARNING! ping when you are stuck. Page 319 STARTING AND OPERATING 317 • If a downshift would cause the engine (+) or left (-), unless an engine lugging
or overspeed •... 14. Such damage is starting and vehicle fuel economy. Inspect front suspension, tie rod ends, boot seals and replace if necessary. Do not Your leather upholstery can be best preserved by regular use protectants or other products, which may cause cleaning with a damp soft cloth. CAUTION! • The towing distance must not exceed 15
mi (24 km). Electronic Stability Control (ESC) Activation/ come on when the ignition key is turned to the Malfunction Indicator Light —... If the 160 Watt (13 Amp) power rating is exceeded the fuse protecting the system will need to be replaced. Remove the wheel nuts, and pull the wheel and wheel WARNING! covers (where applicable) off the hub
Page 328 326 STARTING AND OPERATING If the "Anti-Lock Brake Warning Light" is on, the brake ABS is activated during braking under certain road or system should be serviced as soon as possible to restore stopping conditions. Page 209 UNDERSTANDING YOUR INSTRUMENT PANEL 207 

List Or Browse Mode ....269 RADIO OPERATION AND
MOBILE PHONES ......274 ..... 428 MAINTAINING YOUR VEHICLE Air Conditioner Maintenance CAUTION! For best possible performance, your air conditioner • It is essential when replacing the cables on the should be checked and serviced by an authorized dealer battery that the positive cable is attached to the at the start of each warm season
Page 286 284 UNDERSTANDING YOUR INSTRUMENT PANEL • Floor The operator can override the AUTO mode setting to change airflow distribution by rotating the following positions. This will allow more engine WARNING! (Continued) torque to be
applied to the wheel that is not spinning. 18 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE 4. small amount flowing through the defrost and •... Grasp the deployed AHR from the rear seat. Do not use additional specified Organic Additive Technology (OAT) en- rust inhibitors or antirust products, as they may not gine coolant (antifreeze)
may result in engine be compatible with the radiator engine coolant and damage and may decrease corrosion protection. MAINTAINING YOUR VEHICLE 421 4. Never leave children in a vehicle, with the keys in For vehicles not equipped with the Electronic Vehicle the ignition switch. Seat der part of the belt to move freely with you under normal
belts are designed to go around the large bones of conditions. This light monitors the ABS. Allowing children to parking brake released, a brake system malfunction be in a vehicle unattended is dangerous for a is indicated. on a jack. 74 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE Event Data Recorder (EDR) These data can help provide a brake system malfunction be in a vehicle unattended is dangerous for a is indicated.
better understanding of the circumstances in which crashes and injuries occur. The OBD II vehicle is started. If the AUX audio sounds distorted, turn the device's volume down. 272 UNDERSTANDING YOUR INSTRUMENT PANEL Previous Track STEERING WHEEL AUDIO CONTROLS — IF EQUIPPED Use the SEEK DOWN button, or press the VR
button on the radio and say "Previous Track" to jump to the previous track music on your cellular phone. Page 248 246 UNDERSTANDING YOUR INSTRUMENT PANEL Supported MP3 File Formats Sampling MPEG Frequency Bit Rate (kbps) The radio will recognize only files with the *.MP3 exten- Specification (kHz) sion as MP3 files. Always
connect the chains to vehicle and the trailer such that the following four the frame or hook retainers of the vehicle hitch. The SELECT Button also resets features. The seat belt latch plate is above the back of the front seat, next to your arm. Store heavier items service as long as you do not exceed the GVWR and the down low and be sure you
distribute their weight as front and rear GAWR. This feature is activated whenever you turn on the rear window defroster. You can select to use a lower priority mobile phone at any time (refer to "Call". L O L 18. 96 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE 5. UNDERSTANDING YOUR INSTRUMENT PANEL 257 AM/FM Button
Supported Media (Disc Types) Press the button to select either AM or FM mode. THINGS TO KNOW BEFORE STARTING YOUR VEHICLE 97 NOTE: A new engine may consume some oil during its WARNING! (Continued) first few thousand miles (kilometers) of operation. Page 223 UNDERSTANDING YOUR INSTRUMENT PANEL 221 Your vehicle
starting off in deep snow, sand or as possible to have the problem diagnosed and corrected. • A poorly fitting gas cap may cause the "Malfunc- tion Indicator Light (MIL)" to turn on. Page 415 WHAT TO DO IN EMERGENCIES 413 • The transmission must be in NEUTRAL. If system may not be ready if your vehicle was recently the problem is detected
twice in a row, the system will serviced, recently had a dead battery or a battery replace- turn on the "Malfunction Indicator Light (MIL)."... SENTRY KEY NOTE: The Sentry Key Immobilizer System prevents unauthor.... Page 498 496 INDEX Jack Operation .....352 Jump Starting . .165 Capacities .....377 Interior . The following
as coats, seat covers or portable DVD players. UNDERSTANDING YOUR INSTRUMENT PANEL 265 Select the button (1-6) you wish to lock onto this channel Buttons 1 - 6 and press and release that button. 174 UNDERSTANDING THE FEATURES OF YOUR VEHICLE NOTE: The mist feature does not activate the washer Headlights With Wipers
Feature (Available With pump; therefore, no washer fluid will be sprayed on the Automatic Headlights Only) windshield. To tilt the head restraint closer to the back of your head, pull forward on the bottom of the head restraint. You might lose control of the vehicle and have a collision. It the performance of the emissions, engine, and automatic could
Page 285 UNDERSTANDING YOUR INSTRUMENT PANEL 283 In form ation Provided by :... When the air conditioning is •... displayed. UNDERSTANDING YOUR INSTRUMENT PANEL 267 NOTE: If the audio device battery is completely dis-Controlling The iPod Or External USB Device charged, it may not communicate with the iPod /USB,
Using Radio Buttons MP3 control system until a minimum charge is attained. 3 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE. Page 389 STARTING AND OPERATING 387 Automatic Transmission noty) before towing. operation, only the language-specific 32-name phone-
book is usable. Please see your authorized dealer for service. How-WARNING! ever, the manufacturer recommends that air conditioning • Use only refrigerants and compressor lubricants service be performed by authorized dealer for service.
Playback of MP3 Files To increase the speed of disc loading, it is recommended to use CD-R media and single-session discs. Headlight glare can be reduced by moving the small control under the mirror to the night position (toward the rear of the vehicle). Never have any smok- ing materials lit in or near the vehicle when remov- ing the fuel filler tube
cap (gas cap) or filling the tank. Without releasing the button proceed with "Program- and observe the indicators These indicators are molded into the bottom of the tread grooves. To get into the
YOUR VEHICLE available which include detailed service information for MAINTENANCE PROCEDURES your vehicle. THINGS TO KNOW BEFORE STARTING YOUR VEHICLE 17 Customer Key from the vehicle and valid Sentry Keys by
Primary Alternate (s) zero call cancel three confirmation prompts four continue five delete dial seven download eight edit nine emergency star (*) English plus (+) erase all pound (#) Espanol add location... The Uconnect Phone will allow you to enter up to 32 names in the phonebook with each name having up to • After the "Ready" prompt and the
following beep, say four associated phone numbers and designations. If these particles settle on or all of the following may occur: your clothing, follow the garment manufacturer's in- structions for cleaning. The cost of such repairs is • All wheels and wheel trim, especially aluminum and considered the responsibility of the owner. Delete/Erase "All
Uconnect Phonebook Entries • After the "Ready" prompt and the following beep, say •... MAINTENANCE SCHEDULE ... service. You will not need to remember this PIN To begin using your Uconnect Phone, you must pair after the initial pairing process. Page 185
hood to close it. not have any accessory items installed which will Air Bag Deployment Sensors And Controls alter the roof, including adding a sunroof to your vehicle. 22 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE • The Illuminated Entry system will not operate if the dimmer control is in the "Dome defeat" position (extreme bottom
position). up on the shoulder belt. lock which requires the shift lever to be placed in PARK before the ignition switch can be turned to the LOCK/ Four-Speed Automatic Transmission —... sounds a signal to remove the key. This • It is extremely dangerous to ride in a cargo area, should be considered a normal part of the break-in and
seat is in the position The manual seat adjustment bar is at the front of the seat, desired. Page 402 400 WHAT TO DO IN EMERGENCIES 6. 324 STARTING WARNING! (Continued) CAUTION! • Never leave children alone in a vehicle, or with If the "Brake Warning Light" remains on with the access to an unlocked vehicle. Page 10 I
n formationProvided by:... 486 IF YOU NEED CONSUMER ASSISTANCE Vehicle Safety Standard No. 109. 464 MAINTAINING YOUR VEHICLE Backup Lamps NOTE: Placing a small flat head screwdriver or similar tool between the lamp outboard ball stud and plastic 1. Reassemble the lug wrench to the jack assem- bly and stow it in the
media supported by the radio are CDDA, CD-R, CD-RW, MP3, and CDDA+MP3. MAINTAINING YOUR VEHICLE 453 Seat Belt Maintenance Cleaning Do not bleach, dye, or clean the belts with chemical Soak the rubber cupholder liner in a mixture of medium solvents or abrasive cleaners. tion. Selecting the cally maintains the climate in the cabin of
the vehicle at "O"... Each air bag deploys independently; a left side impact deploys the left air bag only. With CDDA, CD-R, CD-RW, MP3, and CDDA+MP3. UNDERSTANDING THE FEATURES OF YOUR VEHICLE 171 WINDSHIELD WIPERS AND WASHERS Rotate the end of the lever to the LO
edge of the tail lamp. Mirror Directions When you are finished adjusting the mirror, turn the control to the rear •... If the selected phone is not available, the lowest priority. Removing a mirror. The center belt is mounted to the rear •... If the selected phone is not available, the lowest priority. Removing a mirror. The center belt is mounted to the rear •... If the selected phone is not available, the lowest priority.
should be set for the zone where the vehicle is driven, per the zone map. Page 507 INDEX 505 Warranty Information ..... Using tire chains on the vehicle. STARTING AND OPERATING Tire And Loading Information Placard 3) tire size designed
for your vehicle 4) cold tire inflation pressures for the front, rear, and spare tires. country where the vehicle is purchased (1-800-528- 2069 for the U.S., 1-877-213-4525 for Canada, 55-14- Working With Automated Systems 3454 for Mexico City and 1-800-712-3040 for outside... UNDERSTANDING YOUR INSTRUMENT PANEL 269 • Turning it
clockwise (forward) and counterclockwise SCAN button again. Use only fully shielded Mobile two-way radios and telephone equipment must be installed coaxial cable. Page 50 48 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE WARNING! • A belt that is buckled into the wrong buckle will not protect you properly. Using wheels/tires not
equipped with TPM sensors. Page 94 92 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE 5. Page 294 292 STARTING AND OPERATING FLEXIBLE FUEL (3.6L ENGINE ONLY) — IF VEHICLE LOADING .....376 EQUIPPED ......369 .... This is called "Express Close". UNDERSTANDING YOUR INSTRUMENT PANEL 225 Trip B Shows the total
distance traveled for Trip B since the last reset. WARNING! If the vehicle is moving less than 10 mph (16 km/h), delay times will be doubled. Page 475 MAINTENANCE SCHEDULES 473 Mileage or time passed (whichever comes first) Or Years: Or Kilometers: Replace spark plugs (2.4L Engine). Align the valve notch in the wheel cover with the valve
stem on the wheel. WHAT TO DO IN EMERGENCIES 393 NOTE: There are steps that you can take to slow down WARNING! an impending overheat condition: You or others can be badly burned by hot engine • If your air conditioner (A/C) is on, turn it off. Children should be seated and using the proper restraint system. Page 124 122
UNDERSTANDING THE FEATURES OF YOUR VEHICLE in progress. Page 84 82 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE LATCH Positions For Installing Child Restraints In This Vehicle Lower Anchorage Symbol 2 anchorage Symbol 3 anchorage Symbol 3 anchorage Symbol 3 anchorage Symbol 3 anchorage Symbol 4 anchorage Symbol 4 anchorage Symbol 4 anchorage Symbol 5 anchorage Symbol 6 anchorage Symbol 8 anc
qualified specialist at an authorized dealer. Voice "Voice Training" feature may be used. If this occurs, rotate the key to the right slightly, then remove the key as described. Why 19. before 1995. THINGS TO KNOW BEFORE STARTING YOUR VEHICLE 101 Periodic Safety Checks You Should Make Outside Door Latches The Vehicle Check for positive
closing, latching, and locking. Page 439 MAINTAINING YOUR VEHICLE 437 CAUTION! (Continued) • Do not use water alone or alcohol-based engine • Mixing of engine coolant (antifreeze) products. Use this 4. Center Console Storage The top compartment holds small items, such as a pen and note pad,
control... Page 432 430 MAINTAINING YOUR VEHICLE The A/C Air Filter is located in the fresh air inlet behind 5. Page 90 88 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE 2. Page 143 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 2. Page 143 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 2. Page 143 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 2. Page 143 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 2. Page 143 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 2. Page 143 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 2. Page 143 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 2. Page 143 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 3. Page 143 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 3. Page 143 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 3. Page 143 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 3. Page 143 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 3. Page 143 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 3. Page 143 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 3. Page 143 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 3. Page 143 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 3. Page 143 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 3. Page 143 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 3. Page 143 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 3. Page 143 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 3. Page 143 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 3. Page 143 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 3. Page 143 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 3. Page 143 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 3. Page 143 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 3. Page 143 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 3. Page 143 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 3. Page 143 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 3. Page 143 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 3. Page 143 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 3. Page 143 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 3. Page 143 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 3. Page 143 UNDERSTANDING THE PAGE 3. Page 143 UNDERSTANDING THE PAGE 3. Page 143 UNDERSTANDING THE PAGE 3. Page 143 UN
home record again language redial list names return to main menu return or main menu list phones select mobile send mute set up... MAINTAINING YOUR VEHICLE 441 • Make sure that the coolant expansion bottle overflow WARNING! hoses are not kinked or obstructed. •... If you have any doubt about your ability to perform a service
Adjust the outside mirror to center on the adjacent lane of vehicle seen in the passenger side convex mirror. heat in use. Page 442 440 MAINTAINING YOUR VEHICLE The radiator cap unless checking for evidence of
radiator or hose leaks, the vehicle may be engine coolant (antifreeze) freeze point or replacing cool- safely driven. 376 STARTING AND OPERATING VEHICLE LOADING Gross Vehicle Weight Rating (GVWR) The GVWR is the total allowable weight of your vehicle. Page 401 WHAT TO DO IN EMERGENCIES 399 3. 108 UNDERSTANDING THE
FEATURES OF YOUR VEHICLE Automatic Dimming Mirror — If Equipped This mirror automatically adjusts for headlight glare from vehicles behind you. The long enough. Using a small screwdriver, press inward the locking tab on the side of the lamp assembly and pull down on the lamp assembly for removal. They are recom- mended for your
vehicle in order to help keep the vehicle To contact NHTSA, you may either call the Auto Safety operating at its best. This can 2. Page 88 86 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE Locating The LATCH Anchorages In addition, there are tether strap anchorages behind each rear seating position located in the panel between the rear
seatback and the rear window. Page 136 134 UNDERSTANDING THE FEATURES OF YOUR VEHICLE Send Messages: Uconnect Phone can read or send messages on You can send messages on Y
maximum trailer weight a given trailer hitch class can dustry Standards tow and should be used to assist you in selecting the Class I - Light Duty 2,000 lbs (907 kg) correct trailer hitch for your intended towing condition. Also, be sure the oil fill American Petroleum Institute (API) Engine Oil cap is replaced and tightened after adding oil. As the belt
retracts, you will Equipped hear a clicking sound. Remove and replace the battery. Page 412 410 WHAT TO DO IN EMERGENCIES CAUTION! • When "rocking" a stuck vehicle by shifting be-Racing the engine or spinning the wheels may lead to transmission overheating and failure. Page 451 MAINTAINING YOUR VEHICLE 449 • If you
proper operation, the Elec- WARNING! tronic Speed Control System has been designed to shut down if multiple Speed Control system on the same time. Page 201 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 199 comfort. Start a dialogue by pressing the Voice Command
button. The instrument panel cover has a low glare surface, which minimizes reflections in the windshield. • Towing this vehicle in violation of the above re- quirements can cause severe transmission damage. Do not exceed 5 mph in tight spaces. 354 STARTING WARNING! (Continued) • Failure to equip your vehicle
with tires having • Do not use a tire, wheel size or rating other than adequate speed capability can result in sudden tire that specified for your vehicle. of the seat near the floor. 274 UNDERSTANDING YOUR INSTRUMENT PANEL CD/DVD DISC MAINTENANCE NOTE: If you experience difficulty in playing a particu- lar disc, it may be damaged (i.e.
scratched, reflective To keep a CD/DVD in good condition, take the following coating removed, a hair, moisture or dew on the disc) precautions: oversized, or have protection encoding. the child restraint is allowed, if the child restraint manufacturer also allows contact. Loosen the adjusters on the lower straps and on the 6. Page 147
UNDERSTANDING THE FEATURES OF YOUR VEHICLE 145 • "Menu Radio" (to switch to the AM band, say "AM" or "Radio AM". If the AUX audio limited coverage in Alaska. 386 STARTING AND OPERATING CAUTION! WARNING! (Continued) • Towing any trailer
will increase your stopping If the trailer weighs more than 1,000 lbs (454 kg) distance. When the fuel level drops to approximately 2.0 7. Page 325 STARTING AND OPERATING 323 The parking brake lever is located in the center console. Use all season tires only in sets of four; If you need snow tires, select tires equivalent in size and failure to do so
may adversely affect the safety and type to the original equipment tires. .12 Cleaning . Do not overfill. In this mode, the shoulder belt is automatically pre- locked. Page 504 502 INDEX Automatic Transmission .....24 Taillights .......464 Cold Weather . Frontal Area (GTW) (See Note 1) 2.4L/Auto 11 sq.ft. Page 15 THINGS TO KNOW BEFORE STARTING
YOUR VEHICLE 13 NOTE: • If you try to remove the key before you place the shift lever in PARK, the key may become trapped tempo- rarily in the ignition switch lock cylinder. Send number to call 7. Forces gener- ated by excessive wheel speeds may cause damage, or 4. Always use antifreeze) and operate the system for a few seconds to washer
fluid when using the wipers to remove salt or dirt flush out the residual water. • Unequal tire pressures from one side of the vehicle to drift to the able steering response. Brake Warning Light If brake failure is indicated, immediate repair is neces- sary. Pagean tire pressures from one side of the vehicle to drift to the able steering response.
452 450 MAINTAINING YOUR VEHICLE Cleaning Headlights Stain Repel Fabric Cleaning Procedure - If Equipped Your vehicle is equipped your vehicle is equipped with plastic headlights and fog lights (if equipped than glass headlights. Page 279
Oil Fill 4 — Integrated Power Module (Fuses) 8 —... Connect Or Disconnect Link Between The Uconnect Phone and Mobile Phone In order to un-mute the Uconnect Phone In order to 
openers that were manu- factured after 1995. WARNING! 1. Holding either button will bypass 5. If the CAUTION! (Continued) engine fails to start within 10 seconds, turn the ignition • Do not shift from REVERSE, PARK, or NEUTRAL switch to the LOCK position, wait 10 to 15 seconds, then into any forward gear when the engine is above repeat the
 "Normal Starting"... STARTING AND OPERATING 375 Loose Filler Cap Message WARNING! (Continued) If the vehicles diagnostic system determines that the fuel • Never add fuel when the engine is running. Press the left SEEK button to return to the beginning SET/RND Button (Random Play Button) of the current selection, or return to the
beginning of the Press this button while the CD is playing to activate... Each button can be set for SET 1 and Operation Instructions — CD MODE For CD And SET 2 in both AM and FM. Page 295 STARTING AND OPERATING Starting
Replacement Parts The characteristics of E-85 fuel make it unsuitable for use Many components in your Flexible Fuel Vehicle (FFV) are when ambient temperatures fall below 0°F (-18°C). Seven devices can be paired to the Uconnect phone system, but just one can be selected Do not plug in or remove the iPod or external USB and played. To release
the belt, push the red button on the buckle. 172 UNDERSTANDING THE FEATURES OF YOUR VEHICLE NOTE: The wipers will automatically return to the park cycles desirable. The Uconnect Phone will work the same -... Page 4 I n f o r m a t i o n P r o v i d e d b y :... 244 UNDERSTANDING YOUR INSTRUMENT PANEL SEEK Button AM/FM Button
Press the right SEEK button for the next selection on the Press the button to select either AM or FM mode. STARTING AND OPERATING 383 Towing Requirements WARNING! To promote proper break-in of your new vehicle drive- Improper towing can lead to a collision. .470 I n f o r m a t i o n P r o v i d e d b y :... Pressing and releasing the DOWN
Language button when SYSTEM OK is displayed will do nothing. Insert a blank Sentry Key into the ignition switch. 296 STARTING AND OPERATING If Engine Fails To Start WARNING! (Continued) • If the vehicle has a discharged battery, booster warning with the ignition switch.
liquid into the battery or the battery or the battery in another vehicle. Rotate the bulb's electrical connector one-quarter turn counterclockwise and remove it from the fog lamp 1. The drive wheels could lose their Unequal traction can cause sudden pulling of the grip and the vehicle could skid, causing an accident front wheels. Page 106 104 UNDERSTANDING
THE FEATURES OF YOUR VEHICLE SEATS ......148 LIGHTS ......148 LIGHTS ......148 LIGHTS ......164 ..... Page 66 64 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE When the seat's trim cover. Page 91 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE When the seat's trim cover.
STARTING YOUR VEHICLE 73 • The Air Bag Warning Light remains on after the four to Air Bag Warning Light remains on after the four to Air Bag Warning Light remains on after the four to Air Bag Warning Light remains on after the four to Air Bag Warning Light remains on after the four to Air Bag Warning Light remains on after the four to Air Bag Warning Light remains on after the four to Air Bag Warning Light remains on after the four to Air Bag Warning Light remains on after the four to Air Bag Warning Light remains on after the four to Air Bag Warning Light remains on after the four to Air Bag Warning Light remains on after the four to Air Bag Warning Light remains on after the four to Air Bag Warning Light remains on after the four to Air Bag Warning Light remains on after the four to Air Bag Warning Light remains on after the four to Air Bag Warning Light remains on after the four to Air Bag Warning Light remains on after the four to Air Bag Warning Light remains on after the four to Air Bag Warning Light remains on after the four to Air Bag Warning Light remains on after the four to Air Bag Warning Light remains on after the four to Air Bag Warning Light remains on after the four to Air Bag Warning Light remains on after the four the four to Air Bag Warning Light remains on after the four the f
purchased (911 for the U.S. and gency, your mobile phone must be: Canada and 060 for Mexico). Page 315 STARTING AND OPERATING 313 • With brake pedal released, verify that the shift lever WARNING! (Continued) will not move out of PARK. Page 472 470 MAINTENANCE SCHEDULES MAINTENANCE SCHEDULES than your authorized dealer
WARNING! Overloading of your tires is dangerous. When the ve- 2. Brake Master Cylinder We recommend you use MOPAR DOT 3 and SAE J1703. Page 418 416 MAINTAINING YOUR VEHICLE 

Brake System ......441 

Headlamp ......461 

Headlamp ......461 

Headlamp .....461 

Head
buttons, Programming A Non-Rolling Code repeat each step for each remaining button. Page 313 STARTING AND OPERATING 311 WARNING! (Continued) • It is dangerous to move the shift lever out of PARK • Never use the PARK position as a substitute for the or NEUTRAL if the engine speed is higher than parking brake. This means
the operator can override the blower, the mode, or both. Page 309 STARTING AND OPERATING 307 In the event of a momentary problem, the transmission can be reset to regain all forward gears by performing the Use this range for engine braking when descending very following steps: steep grades. Only the active call(s) will be terminated and if
there is a call on hold, it will become the new active call. driver of a low tire pressure based on the vehicle recom- mended cold placard pressure. If the "Anti-Lock Brake clude ice, snow, gravel, bumps, railroad tracks, loose Warning Light"... Page 93 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE 91 Can the rear-facing child restraint touch
the Contact between the front passenger seat and back of the front passenger seat? Page 46 44 THINGS TO KNOW BEFORE STARTING VOUR VEHICLE You should read the instructions provided with your WARNING! child restraint to make sure that you are using it properly. Page 310 308 STARTING AND OPERATING If the transmission cannot be
equipped with the child restraint anchor- Restraint System age system called LATCH, which stands for Lower Anchors and Tethers for CHildren. is not loud enough, turn the device's volume up. Engine oil is an engineered product and its quality filters should be used to assure most efficient performance may be impaired by supplemental additives. 3
- Final Downward Movement To Engage Locking Mechanism 1 — Downward Movement I n f o r m a tion Provided the cover. UNDERSTANDING THE FEATURES OF YOUR VEHICLE 111 Heated Mirrors — If Equipped These mirrors
are heated to melt frost or ice. As with all vehicles, move the shift lever rearward (with the brake pedal you should never exit a vehicle while the engine is released) after you have placed it in PARK. THINGS TO KNOW BEFORE STARTING YOUR VEHICLE 27 1. To lengthen or upward or downward. ESC cor- ics from acting on the vehicle, nor can it
increase rects for over/under steering of the vehicle by applying braking efficiency beyond that afforded by the the brake of the appropriate wheel to assist in counter... 396 WHAT TO DO IN EMERGENCIES 6. mobile, or other) that you wish to edit. 294 STARTING AND OPERATING PROCEDURES WARNING! (Continued) Before starting
jacking on locations other than those indicated in Step 3. Page 217 UNDERSTANDING YOUR INSTRUMENT PANEL 215 The two trip odometers show individual trip mileage. The Electronic Speed Control buttons are located on the right side of the steering wheel. When this happens, the connection ON or ACC position, or after a language change,
you can generally be reestablished by switching the phone must wait at least fifteen seconds prior to using the off/on. • The towing speed must not exceed 25 mph (40 km/h). Anti-Lock Brake (ABS) Light — If Equipped should come on. Make sure the air intake, located directly in front of the windshield, is free of obstructions such as leaves. For •
Always park on a firm, level surface as far from the example, if changing the right front edge of the roadway as possible before raising the tire, block the left rear wheel. Page 314 312 STARTING AND OPERATING WARNING! (Continued) CAUTION! • When leaving the vehicle, always remove the key • Before moving the shift lever out of PARK, you
fob from the ignition and lock your vehicle. MAINTAINING YOUR VEHICLE 443 WARNING! (Continued) • To avoid contaminate moisture, use only new brake fluid to contamination from foreign matter or • Do not allow petroleum based fluid to contaminate moisture, use only new brake fluid or fluid that has the brake fluid. to one, indicating the change. If the medium
       ains a lot of folders or files, the radio will take more MPEG-1 Audio 48, 44.1, 32 320, 256, 224,... Chrysler Group LLC does not recommend deac- Seat Belt Extender tivating BeltAlert . limits of local traffic laws contributes to a good break-in. Page 287 UNDERSTANDING YOUR INSTRUMENT PANEL 285 • Air Conditioner Control NOTE:
the ignition switch is turned to the LOCK Press this button to turn on the air conditioning during manual operation position, the recirculation feature will be cancelled. • Remove any metal jewelry such as watch bands or bracelets that might make an inadvertent electrical contact. battery will discharge sufficiently to degrade battery 9. STARTING
AND OPERATING 339 Tire Loading And Tire Pressure Tire And Loading Information Placard Location NOTE: The proper cold tire inflation pressure is listed on the driver's side B-Pillar or the rear edge of the driver's side door. In the designed to be compatible with ethanol. UNDERSTANDING YOUR INSTRUMENT PANEL 249 Operating Instructions
- Radio Mode SEEK Buttons Press and release the SEEK buttons to search for the next NOTE: The ignition switch is located on the In any of the
following situations, you can reduce the instrument panel, below the radio. Finally, pull up on any excess webbing to tighten the Latch Plate (CINCH) — If Equipped lap portion around the child restraint while you push the child restraint to the 1. Remove the wheel blocks and lower the jack until it is Road Tire Installation
free. 192 UNDERSTANDING THE FEATURES OF YOUR VEHICLE Sunroof Maintenance ELECTRICAL POWER OUTLETS Use only a non-abrasive cleaner and a soft cloth to clean There are two 12 Volt (13 Amp) electrical power outlets on the glass panel. WHAT TO DO IN EMERGENCIES CONTENTS 

Road Tire Installation ....402 HAZARD
WARNING FLASHERS ...392 IF YOUR ENGINE OVERHEATS . Page 82 80 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE Recommendations For Attachment method shown with an "X" Below Weight of the LATCH - Seat Belt Only LATCH - Seat Belt + Top Child + Child Lower
Anchors Lower Anchors Tether Anchor... such as steel wool or scouring powder that will scratch metal and painted surfaces. For large numbers multisession for CD audio or MP3 playback may result in of files and/or folders, the radio may be unable to longer disc loading times. and maintenance, or to provide warning of a tire failure or condition.
With the RKE transmitter buttons facing down, use a 2. Rotating the dial left can select either a primary mode as into the blue area of the scale indicates identified by the symbols on the con-... 26 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE NOTE: If there is no key in the ignition switch, pressing The Panic Alarm will stay on for three
minutes unless the LOCK button on the RKE transmitter while you are in you turn it off by pressing the PANIC button a second the vehicle Security Alarm. UNDERSTANDING YOUR INSTRUMENT PANEL 209 INSTRUMENT CLUSTER I n f o r m a t i o n P r o v i d e d b y :... "Advanced Phone Connectivity" in this section).
UNDERSTANDING THE FEATURES OF YOUR VEHICLE 191 NOTE: If three consecutive sunroof close attempts re- Wind Buffeting sult in Pinch Protect reversals, the fourth close attempt Wind buffeting sult in Pinch Protect reversals, the fourth close attempt with Pinch Protect reversals, the fourth close attempts re- Wind Buffeting sult in Pinch Protect reversals, the fourth close attempt with Pinch Protect reversals.
disabled. UNDERSTANDING THE FEATURES OF YOUR VEHICLE 161 WARNING! The rear cargo area of the vehicle (with the rear seatbacks in the locked-up or folded down position) should not be used as a play area by children. 42 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE • Knee bolsters/blockers for front seat occupants
OCCUPANT RESTRAINTS • Front seat belts incorporate pretensioners that may Some of the most important safety features in your vehicle are the restraint systems: enhance occupant protection by managing occupant energy during an impact event •... Put heavier WARNING! (Continued) objects as low and as far forward as possible. 316 STARTING
AND OPERATING Torque Converter Clutch AUTOSTICK — IF EQUIPPED A feature designed to improve fuel economy has been AutoStick is a driver-interactive transmission on your vehicle. Page 494 492 INDEX Emergency, In Case of Jump Starting ......405 Jacking ......394 Oil . Page 289
UNDERSTANDING YOUR INSTRUMENT PANEL 287 adequate system is started again. Page 49 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE 47 Lap/Shoulder Belt Operating Instructions 1. Remove slack in the tether strap according to the
child While cruising, brief full-throttle acceleration within the restraint manufacturer's instructions. 394 WHAT TO DO IN EMERGENCIES NOTE: The vehicle speed is reduced to a maximum of WARNING! (Continued) 53 mph (85 km/h). Press the LOCK button on a programmed RKE trans- To Lock The Doors mitter for at least 4 seconds, but not
longer than 10 seconds. The six-speed trans- The DRIVE range can be selected when towing. Page 406 404 WHAT TO DO IN EMERGENCIES 6. Prior to the cover, make sure the retaining tabs fully engage the application of any lubricant, the parts concerned should cover. There is a front and rear jacking location on each side of the vehicle.
ELECTRONIC VEHICLE INFORMATION CENTER (EVIC) — IF EQUIPPED The Electronic Vehicle Information Center (EVIC) fea- tures a driver-interactive display that is located in the instrument cluster. Selecting high beam headlights will turn off the front fog lights. Page 505 INDEX 503 Jacking ......394 24-Hour Towing Assistance ....125 Life of
Tires . Page 284 282 UNDERSTANDING YOUR INSTRUMENT PANEL Manual Operation This system offers a full complement of manual override features, which consist of Blower Preferred Automatic, or Blower and Mode Pre- ferred Automatic. Page 196 194 UNDERSTANDING THE FEATURES OF YOUR VEHICLE NOTE:
To ensure proper operation a MOPAR knob and element must be used. If you do not read this entire Owners Manual, you may miss important information. 260 UNDERSTANDING YOUR INSTRUMENT PANEL To increase the speed of disc loading, it is recommended Press the INFO button once more to return to elapsed to use CD-R media and single-
session discs. Leaves Window Fogging collected in the air intake may reduce airflow, and if they Interior fogging on the windshield can be quickly removed... Page 139 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 137 I n f o r m a t i o n P r o v i d e d b y :... You can also turn the Temperature control to maximum heat, the Mode control to
Floor and 1. Press 3. This passenger's Advanced Front Air Bag is mounted in the extender should be used only if the existing belt is not instrument panel, above the glove compartment. .485 PUBLICATION ORDER FORMS ... MAINTAINING YOUR VEHICLE 417 ENGINE COMPARTMENT — 2.4L 1 — Engine Coolant Reservoir 7 — Air Cleaner Filter 2
- Power Steering Fluid Reservoir 8 - Engine Oil Fill 3 - Automatic Transmission Dipstick 9 - Coolant Pressure Cap 4 - Brake Fluid Reservoir 10 -... 461 Key ....... UNDERSTANDING YOUR INSTRUMENT PANEL 275 CLIMATE CONTROLS The Manual
Temperature Controls consist of a series of outer rotary dials and inner push knobs. 368 STARTING AND OPERATING Carbon Monoxide Warnings CAUTION! (Continued) • An out-of-tune engine or certain fuel or ignition WARNING! malfunctions can cause the catalytic converter to Carbon monoxide (CO) in exhaust gases is deadly. The sudden
movement of the seat could cause you to lose control. Bye for now 5. WHAT TO DO IN EMERGENCIES 409 8. Be sure to keep your foot on the brake pedal when The shift lever between these gears. 298 STARTING AND OPERATING ARTOR OPERATING AFTER STARTING ARTOR OPERATING AFTER STARTING AFTER STARTIN
automatically and it will Remember to disconnect the engine block heater decrease as the engine warms up. Always be sure range of 0°F (-18°C) to 32°F (0°C), you may experience an that your vehicle is serviced with correct ethanol com- increase in the time it takes for your engine to start, and... Page 13 THINGS TO KNOW BEFORE STARTING
YOUR VEHICLE 11 - Automatic Locking Retractor Mode - Air Bag Deployment Sensors And Controls ...66 (ALR) — If Equipped ....53 .... Page 79 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE 77 Infants And Child Restraints reach the highest weight or height allowed by their convertible child seat. UNDERSTANDING THE FEATURES OF
YOUR VEHICLE 129 • Following the beep, say "Mute". a new message: • Press the Read Messages: button. The front fog light switch is on the multifunction lever. WHAT TO DO IN EMERGENCIES 405 5. 4. The optional ash receiver also comes with a cigar lighter that can be used with the power outlets. Page 252 250 UNDERSTANDING YOUR
INSTRUMENT PANEL If your vehicle is not equipped with 1. During extremely cold tempera- sixth gear. ..301 STARTING PROCEDURES .... 154 UNDERSTANDING THE FEATURES OF YOUR VEHICLE Driver Seat
Manual Height Adjuster — If Reclining Seats Equipped The recline lever is located on the seat up, down, forward, rearward, or to tilt the seat up, down, forward, rearward, or to tilt the seat up, down, forward, rearward, or to tilt the seat up, down, forward, rearward, or to tilt the seat up, down, forward, rearward, or to tilt the seat up, down, forward, rearward, or to tilt the seat up, down, forward, rearward, or to tilt the seat up, down, forward, rearward, or to tilt the seat up, down, forward, rearward, or to tilt the seat up, down, forward, rearward, or to tilt the seat up, down, forward, rearward, or to tilt the seat up, down, forward, rearward, or to tilt the seat up, down, forward, rearward, or to tilt the seat up, down, forward, rearward, or to tilt the seat up, down, forward, rearward, or to tilt the seat up, down, forward, rearward, or to tilt the seat up, down, forward, rearward, or to tilt the seat up, down, forward, rearward, or to tilt the seat up, down, forward, rearward, or to tilt the seat up, down, forward, rearward, or to tilt the seat up, down, forward, rearward, or to tilt the seat up, down, forward, rearward, or to tilt the seat up, down, forward, rearward, or to tilt the seat up, down, forward, rearward, or to tilt the seat up, down, forward, rearward, or to tilt the seat up, down, forward, rearward, or to tilt the seat up, down, forward, rearward, or to tilt the seat up, down, forward, rearward, or to tilt the seat up, down, forward, rearward, or to tilt the seat up, down, forward, rearward, or to tilt the seat up, down, forward, rearward, or to tilt the seat up, down, forward, rearward, or to tilt the seat up, down, forward, rearward, or to tilt the seat up, down, forward, rearward, or to tilt the seat up, down, forward, rearward, or to tilt the seat up, down, forward, rearward, or to tilt the seat up, down, forward, rearward, rearward,
3. Grasp the latch plate and pull out the belt. Damage to the fascia will occur. 178 UNDERSTANDING THE FEATURES OF YOUR VEHICLE To Deactivate Pressing the RES (+) button until the hours blink. A single chime will sound if the light Inflator Units
comes on again after initial startup. Page 89 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE 87 tether strap. When it comes to service, remember that your new Chrysler Group nicians and genuine MOPAR parts, and cares about LLC
vehicle. Until repaired, drive with all side windows fully open. As with all vehicles, access to an unlocked vehicle. Once the track to be played is highlighted on the radio display, press the •... This compass is self-calibrating, which eliminates the need to calibrate the compass manually. Dam- towing is the preferred towing method. Page 290 288
UNDERSTANDING YOUR INSTRUMENT PANEL Control Setting Suggestions for Various Weather Conditions In form at i on Provide dby:... Do not place any article under a power seat or Moving a seat while driving could result in loss of impede its ability to move as it may cause damage to control which could cause a collision and serious
the seat controls. UNDERSTANDING YOUR INSTRUMENT PANEL 227 MENU Button to accept the display to each of the EVIC Main Menu a selection. UNDERSTANDING THE FEATURES OF YOUR VEHICLE CONTENTS - Phone Call Features
....121 MIRRORS ......107 .... Have any abnormal conditions repaired promptly. The wash function must be used in order to When this feature is active, the headlights will turn on spray the windshield with washer fluid. Page 491 INDEX 489
Automatic Transmission ....298 Brake System ......441 Adding Fluid . Use this mode with maxi- NOTE: For all settings, except full cold or full hot, mum blower and temperature settings for best wind- there is a difference in temperature settings for best wind- there is a difference in temperature settings.
gear range, wait a moment to allow the selected gear to engage before accelerating. 168 UNDERSTANDING THE FEATURES OF YOUR VEHICLE Fog Lights on low beam. .426 ENGINE COMPARTMENT — 2.4L ..417 ... Press and release the REMOTE START button on
the RKE transmitter twice within five sec- Remote start will also cancel if any of the following occur: onds. Allowing children to you should never exit a vehicle while the engine is be in a vehicle unattended is dangerous for a running. UNDERSTANDING YOUR INSTRUMENT PANEL 229 flash in the EVIC display for approximately five seconds NOTE:
If the indicator message illuminates when you after a single chime has sounded to indicate the next start the vehicle, the oil change indicator system did not scheduled oil change interval. Page 299 STARTING AND OPERATING 297 With Tip Start CAUTION! If the engine fails to start after you have followed the To prevent damage to the starter, do
not crank the "Normal Starting" or "Extreme Cold Weather" proce- engine for more than 15 seconds at a time. WHAT TO DO IN EMERGENCIES 411 3. 62 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE Air Bag System Components Advanced Front Air Bag Features Your vehicle may be equipped with the following air bag The Advanced
Front Air Bag system has multistage system components: driver and front passenger air bags. Page 97 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE 95 3. The engine oil change indicator system is duty cycle based, which means the gASCAP engine oil change interval may fluctuate dependent upon If the vehicle diagnostic system detects a
leak or change... Rear Seat Release Loops When returning the rear seatback to the upright position, be sure the seatback is latched. The use of names and folder names is limited. Page 256 254 UNDERSTANDING YOUR INSTRUMENT PANEL AM/FM Button and 12 FM stations to be stored into pushbutton memory. Before leaving the vehicle, make
sure that the parking This is due to the cold, thick fluid in the steering brake is fully applied. Flatbed ments can cause severe transmission damage. Struck by an object such as a hand, foot or loose cargo. Extended use of this mode is not recommended. Items plugged into this power outlet may discharge the battery and/or A second power outlet is
located inside the center con- prevent the engine from starting. STARTING AND OPERATING 345 stability of the vehicle and can produce a feeling of WARNING! (Continued) sluggish response or over responsiveness in the steering. Page 499 INDEX 497 Instrument Cluster ..... Adjust the mirror to center on the view through the rear window. Riding
the brakes can lead to brake failure and • Keep the front of the radiator clean. The sunroof will close fully and stop automati- cally. The AHR front soft foam and trim half should lock into the back decorative plastic half. Enter the vehicle and close the door, Page 119 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 117 • Press the button to
begin. Page 302 300 STARTING AND OPERATING WARNING! (Continued) • Unintended movement of a vehicle could injure • Never leave children alone in a vehicle could injure • Never leave children alone in a vehicle could injure • Never leave children alone in a vehicle could injure • Never leave children alone in a vehicle could injure • Never leave children alone in a vehicle could injure • Never leave children alone in a vehicle could injure • Never leave children alone in a vehicle could injure • Never leave children alone in a vehicle could injure • Never leave children alone in a vehicle could injure • Never leave children alone in a vehicle could injure • Never leave children alone in a vehicle could injure • Never leave children alone in a vehicle could injure • Never leave children alone in a vehicle could injure • Never leave children alone in a vehicle could injure • Never leave children alone in a vehicle could injure • Never leave children alone in a vehicle could injure • Never leave children alone in a vehicle could injure • Never leave children alone in a vehicle could injure • Never leave children alone in a vehicle could injure • Never leave children alone in a vehicle could injure • Never leave children alone in a vehicle could injure • Never leave children alone in a vehicle could injure • Never leave children alone in a vehicle could injure • Never leave children alone in a vehicle could injure • Never leave children alone in a vehicle could injure • Never leave children alone in a vehicle could injure • Never leave children alone in a vehicle could injure • Never leave children alone in a vehicle could injure • Never leave children alone in a vehicle could injure • Never leave children alone in a vehicle could injure • Never leave children alone in a vehicle could injure • Never leave children alone in a vehicle could injure • Never leave children alone in a vehicle could injure • Never leave children alone in a vehicle could injure • Never leave children alone in a vehicle could injure • Never l
all channels should only be performed when Be sure that your vehicle is parked outside of the garage before you begin programming. vehicle's seat belt alone: 5. Page 57 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE 55 How The Active Head Restraints (AHR) Work The Occupant Restraint Controller (ORC) determines whether the
severity, or type of rear impact will require the Active Head Restraints (AHR) to deploy. Temporary high pressure • P (Passenger) - Metric tire sizing is based on U.S. compact spare tires have the letter "T" or "S" molded design standards. Page 63 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE 61 NOTE: The Driver and Passenger Advanced
Front Air This vehicle is equipped with Supplemental Side Air Bag Bags are certified to new Federal regulations. Page 345 STARTING AND OPERATING 343 In formation available when CD may remain in the radio while in the Satellite radio calling: mode. A label that identifies each
component may be printed on the inside of the cover. Page 261 UNDERSTANDING YOUR INSTRUMENT PANEL 259 Playback of MP3 Files Sampling MPEG Frequency Bit Rate (kbps) When a medium containing MP3 data is loaded, the Specification (kHz) radio checks all files on the medium. 32 THINGS TO KNOW BEFORE STARTING YOUR
VEHICLE WARNING! CAUTION! • For personal security and safety in the event of an An unlocked vehicle is an invitation to thieves. 208 UNDERSTANDING YOUR INSTRUMENT PANEL FEATURES 1 — Air Outlet 6 — Radio 11 — Storage Compartment 2 — Side Window Demister Outlet 7 — Passenger Airbag 12 — Climate
```

```
Control 3 — Instrument Cluster 8 — Glove Compartment 13 — ... CAUTION! • Do not exceed the maximum power of 160 Watts (13 Amps) at 12 Volts. Page 441 MAINTAINING YOUR VEHICLE 439 rules for your community. Page 1 2 0 1 3 O W N E R'S M A N U A L I n f o r mation Provided the maximum power of 160 Watts (13 Amps) at 12 Volts. Page 441 MAINTAINING YOUR VEHICLE 439 rules for your community.
Locate the connector behind the headlamp. causes the tuner to search for the next channel in the direction of the arrows. MAINTAINING YOUR VEHICLE 427 Engine Air Cleaner Filter Selection To access the battery, turn the steering wheel fully to the right and remove the inner fender shield. This can happen (SABIC) and Seat-Mounted Side Air
 Bags (SAB) far away from home or on your own street. Page 506 504 INDEX Automatic ......298 Unleaded Gasoline ......364 Filter. THINGS TO KNOW BEFORE STARTING YOUR VEHICLE 75 Child Restraints Before buying any restraint system, make sure that it has a label certifying that it meets all applicable Safety Everyone in your vehicle needs to
be buckled up at all Standards. The resulting figure equals the available amount of vehicle, locate the statement "The combined weight of cargo and luggage load capacity. Page 70 68 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE turns on the Air Bag Warning Light, either momentarily Driver And Passenger Advanced Front Air Bag or
continuously. When in this display you may select different languages Displays SYSTEM WARNINGS PRESENT if there are for all display nomenclature, including the trip functions. Wide-open throttle acceleration in low gear can be detri-
another selection. Jamming due to electronic devices or driving next to 20 minutes above 15 mph (24 km/h) in order for the facilities emitting the same Radio Frequencies as the TPMS to receive this information. Do not use volatile solvents for cleaning purposes. DO NOT keeping the HomeLink indicator light in view. UNDERSTANDING THE
FEATURES OF YOUR VEHICLE 113 Uconnect Phone Button The Uconnect Phone is fully integrated with the vehi- cle's audio system. 142 UNDERSTANDING THE FEATURES OF YOUR VEHICLE General Information VOICE COMMAND — IF EQUIPPED This device complies with Part 15 of the FCC rules and Voice Command System Operation RSS
210 of Industry Canada. 40 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE open or partially open positions. MAINTAINING YOUR VEHICLE 63 Supplemental Seat-Mounted Side Air Bags (SAB) WARNING! Supplemental Seat-Mounted Side Air Bags (SA
(SAB) may • No objects should be placed over or near the air provide enhanced protection to help protect an occupant bag on the instrument panel, because any such during a side impact. Place the filter: 1. Page 291 STARTING AND OPERATING CONTENTS 

Brake/Transmission Shift Interlock System. Use a firm downward push at the center of
the hood to ensure that both latches engage. Page 118 116 UNDERSTANDING THE FEATURES OF YOUR VEHICLE • After the "Ready" prompt and the following beep, say phone when you make a call. Do not check oil level CAUTION! (Continued) before starting the engine after it has sat overnight. The air bag may inflate accidentally or may •
Modifications to any part of the air bag system not function properly if modifications are made. Rotate the bulb's electrical connector one-quarter turn 2. Press and release the • Personal Settings compass button to display one of eight compass button 
steering It also includes diagnostics that will illuminate the instru-... Page 473 MAINTENANCE SCHEDULES 471 • Check function of all interior and exterior lights At Every Oil Change Interval As Indicated By Oil
original equip- Full Size Spare - If Equipped ment tire should be repaired (or replaced) and reinstalled The full size spare is for temporary emergency use only. This will weaken the fabric. Page 160 158 UNDERSTANDING THE FEATURES OF YOUR VEHICLE • In the event of deployment of an Active Head Re- straint, refer to "Occupant
Restraints/Resetting Active Head Restraints (AHR)" in "Things to Know Before Starting Your Vehicle" for further information. Page 101 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE 99 Front seat belt assemblies must be replaced after a feel the air directed against the windshield. Damage to the 110-115 Volt electrical cord could cause
protect the driver, front, and rear passengers sitting next to a window. Additional Maintenance Replace engine air filter. UNDERSTANDING YOUR INSTRUMENT PANEL 261 NOTE: The AUX device must be turned on and the NOTE: Sirius service is not available in Hawaii and has device's volume set to the proper level. STARTING AND OPERATING
KEYS ... Turn the TUNE/SCROLL control Display knob to the left or right to adjust the sound level between No program type or None the front and rear speakers. Loosen, but do not remove, the wheel is still on the ground. Insert the tip of the ignition key or similar flat-bladed object into the
lock and rotate approxi- Avoid trapping anyone in a vehicle in a collision. STARTING AND OPERATING 347 loading may be required for high-speed vehicle opera- Radial Ply Tires tion. Stamped VIN Location NOTE: It is illegal to remove or alter the VIN. Page 138 136 UNDERSTANDING THE FEATURES OF YOUR VEHICLE Bluetooth Communication
Link Power-Up Mobile phones have been found to lose connection to the After switching the ignition key from OFF to either the Uconnect Phone. A light to the left of the button will illuminate to indicate when the dimming feature is activated. Squeeze one side WARNING! of the liner's center to expose its edge and facilitate removal. 432
MAINTAINING YOUR VEHICLE Operation of the wipers on dry glass for long periods reservoir with windshield washer solvent (not radiator may cause deterioration of the wiper blades. Grades B and A repre- WARNING! sent higher levels of performance on the laboratory test wheel, than the minimum required by law. 124 UNDERSTANDING THE
FEATURES OF YOUR VEHICLE • An active call is automatically transferred to the mo-NOTE: After every Uconnect Phone language change bile phone after the ignition is cycled to OFF. The guality of replacement engine air cleaner filters varies considerably, services determined by the engineers who designed your vehicle. If using another vehicle to
 jump-start the battery, park (+) battery post. Inspect the brake linings, parking brake function. 460 MAINTAINING YOUR VEHICLE REPLACEMENT BULBS Exterior Bulbs Bi-Halogen HIR2 Bulb Number Headlamp Front Courtesy/ 578/W5W Front Turn 3157NAK Reading Lamp Signal Lamp Center Courtesy/ 578/W5W
 Front Park Lamp Reading Lamp (Serviced at Authorized Dealer) Visor Vanity Lamp A6220 Front Fog Lamp Glove Box Lamp... Avoid touching the flat blade screwdriver to pry the two halves of the RKE new battery with your fingers. Page 283 UNDERSTANDING YOUR INSTRUMENT PANEL 281 • If your air conditioning performance seems lower
 than Blower Control expected, check the front of the A/C condenser located in front of the radiator for an accumulation of dirt or For full automatic operation or for insects. Once properly set, the compass will automatic operation or for insects. Once properly set, the compass will automatically compensate for the differences and provide the most accumulation of the A/C condenser located in front of the A/C condenser located in front of the accumulation of dirt or For full automatically compensate for the differences and provide the most accumulation of the A/C condenser located in front of the A/C condenser located in front of the accumulation of dirt or For full automatic approximation of the A/C condenser located in front of the A/C condens
Towing Requirements - Tires replacement procedures. Sensors, mounted to each Tire Pressure Monitoring Low Pressure Warnings wheel as part of the valve stem, transmit tire pressure readings to the Receiver Module. UNDERSTANDING THE FEATURES OF YOUR VEHICLE 109 Power Mirrors The power mirror control is located on the driver's
door trim panel. 54 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE Energy Management Feature NOTE: These devices are not a substitute for proper seat belt placement by the occupant. Lower the armrest and The rear window defroster button is located on pull downward on the latch to open the ski pass-through the climate control
(Mode) knob. .482 Windows ...... 328 STARTING AND OPERATING brake of the spinning wheel. inflates. Position the latch plate as close as possible to the anchor point. 228 UNDERSTANDING YOUR INSTRUMENT PANEL • RKE (Remote Keyless Entry) Battery Low (with a • Remote start aborted — Hood ajar single chime) • Remote start aborted
 Trunk ajar • Personal Settings Not Avail - Vehicle Not In PARK •... Page 447 MAINTAINING YOUR VEHICLE 445 Fluid Level Check - Four-Speed Transmission 6. • After the "Phonebook Delete". Stop the vehicle. THINGS TO KNOW BEFORE
STARTING YOUR VEHICLE 15 Key-In-Ignition Reminder key forward. ** Replace spark plugs (3.6L Engine). Page 51 THINGS TO KNOW BEFORE STARTING YOUR INSTRUMENT PANEL Push the rotary TUNE/SCROLL control knob a fifth time 16-Digit Character Program Type and FADE will
display. All occupants should always wear their lap and severe injuries in a collision. 242 UNDERSTANDING YOUR INSTRUMENT PANEL display window. RW/FF TIME Button Pressing the RW (Rewind) or FF (Fast Forward) buttons Press the TIME button to alternate display of the time causes the tuner to search for the next frequency in the and
radio frequency. All systems work together to enhance WARNING! vehicle stability and control in various driving conditions and are commonly referred to as ESC. Page 474 472 MAINTENANCE SCHEDULES Maintenance Chart Mileage or time passed (whichever comes first) Or Years: Or Kilometers: Additional Inspections Inspect the CV joints.
collision, lock the vehicle doors as you drive as Always remove the key from the ignition and lock all well as when you park and leave the vehicle may have a recommended warning have been established for the tire size cold (parked for more than three hours) placard pressure... • Relying on the air bags
alone could lead to more 2. This system provides •... This light will 24. Page 78 76 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE Summary Of Recommendations For Restraining Children who are two years old or Either an
Infant Carrier or a Convertible younger and who have not reached the Child Restraint, facing rearward in the rear height or your body, and to have the air bags ready to inflate for your protection in a collision. The lap portion could ride too high on your body,
possibly causing internal injuries. 348 STARTING AND OPERATING THE FEATURES OF YOUR VEHICLE 157 Push Button Active Head Restraint (Normal Position) For comfort the Active Head Restraints can be tilted forward and rearward. UNDERSTANDING THE FEATURES OF YOUR VEHICLE 153
Manual Front Seat Adjustment Pull the bar upward to move the seat forward or rear- ward. If your vehicle is equipped with adjustable rear head restraints, raise the head restraint, and where possible, route the tether strap under the head restraint, and between the two posts. The side curtain air bag is only about 3-1/2 in (9 cm) thick when • Flash
hazard lights as long as the battery has power or it is inflated. Page 476 474 MAINTENANCE SCHEDULES Mileage or time passed (whichever comes first) Or Years: Or Kilometers: Change automatic transmission fluid and filter if using your ve- hicle for any of the following: po- lice, taxi, fleet, or frequent trailer towing. potential for overheating by
taking the appropriate ac- tion. 144 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 459 VEHICLE 459 VEHICLE STORAGE CAUTION! If you will not be using your vehicle for more than 21 • When installing theat the first available Menu, press the Voice Com- Main Menu". MAINTAINING YOUR VEHICLE 459 VEHICLE 459 VEHICLE 500 VEHICL
Integrated Power Module days, you may want to take steps to preserve your cover, it is important to ensure the cover is properly battery. Non-MP3 files named with the *.MP3 extension may cause playback problems. UNDERSTANDING YOUR INSTRUMENT PANEL 271 device first, then it will get streamed to the Uconnect WARNING! phone system
UNDERSTANDING THE FEATURES OF YOUR VEHICLE 167 NOTE: If either light remains on and does not flash, or Flash-To-Pass there is a very fast flash rate, check for a defective outside You can signal another vehicle with your headlights by light bulb. Engine Oil Filter. Page 322 320 STARTING
AND OPERATING CAUTION! (Continued) • Driving through standing water may cause damage • Always check the depth of the standing water to your vehicle's drivetrain components. Page 37 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE 35 Child-Protection Door Lock Location Child Lock Control The Child-Protection Door
Locks are located inside the WARNING! rear edge of the door. 224 UNDERSTANDING YOUR INSTRUMENT PANEL Control Buttons RESET Button To reset the display shown, turn the ignition switch to the ON position, then press and hold the RESET button located on the steering wheel. Page 96 94 THINGS TO KNOW BEFORE STARTING YOUR
VEHICLE If the buckle or the cinching latch plate is too close to the Installing Child Restraints Using The Top Tether belt path opening of the child restraint, you may have Anchorage trouble tightening the seat belt. 162 UNDERSTANDING THE FEATURES OF YOUR VEHICLE TO OPEN AND CLOSE THE HOOD 2. Press and hold the programmed
HomeLink button 3. Turn the TUNE/SCROLL exit setting tone, balance, and fade. Page 87 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE 85 Locating The LATCH Anchorages are round bars that are found at the rear of the seat cushion where it meets the seatback, below the anchorages are round bars that are found at the rear of the seat cushion where it meets the seatback, below the anchorage sym- bols on the seatback. Page 87 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE 85 Locating The LATCH Anchorages are round bars that are found at the rear of the seatback.
188 186 UNDERSTANDING THE FEATURES OF YOUR VEHICLE • To program the two remaining HomeLink buttons, 2. Keep this in mind when checking tire pressure inside a garage, especially in After inspecting or adjusting the tire pressure.
FEATURES OF YOUR VEHICLE CIGAR LIGHTER AND ASH RECEIVER — IF EQUIPPED An optional ash receiver is available from your authorized dealer and will fit in the center console front cupholder. STARTING AND OPERATING 327 Control (ESC). ENGINE BLOCK HEATER —... If you notice a pungent burning odor or Follow the precautions
below to prevent carbon some light smoke, your engine may be out of tune monoxide poisoning:... Refer to "Power Window Switches The control on the driver's door has up/down switches that give you fingertip control of all four power windows."
dows. Once you repair or replace the original road tire, and reinstall it on the vehicle in place of the compact spare, including interference that may cause undesired the TPMS will update automatically. Route the tether strap to provide the most direct path for the strap between the anchor and the child seat. Page 239 UNDERSTANDING YOUR
INSTRUMENT PANEL 237 NOTE: Turning the headlights on during the daytime Illumin. If the buffeting occurs with and release the TRUNK button on the RKE transmitter the rear windows open, then open the front and release the TRUNK button on the RKE transmitter the rear windows open, then open the front and release the TRUNK button on the RKE transmitter the rear windows open, then open the front and release the TRUNK button on the RKE transmitter the rear windows open, then open the front and release the TRUNK button on the RKE transmitter the rear windows open, then open the front and release the TRUNK button on the RKE transmitter the rear windows open, then open the front and release the TRUNK button on the RKE transmitter the rear windows open.
Whenever a change is noticed in the sound of the exhaust WARNING! (Continued) system, when exhaust fumes can be detected inside the eventually poison you. STARTING AND OPERATING 381 Trailer Towing Weights (Maximum Trailer Weight Ratings) The following chart provides the maximum trailer weight ratings towable for your given
drivetrain. Page 332 330 STARTING AND OPERATING ESC Operating Modes WARNING! All ESC equipped vehicles can choose the following ESC Electronic Stability Control (ESC) cannot prevent the operating modes: natural laws of physics from acting on the vehicle, ESC On nor can it increase the traction afforded by prevailing road conditions.
delete all phone pairing, phone book entries, and other settings in all language modes. on your vehicle after overnight parking for
fuel, patterns. I need more direction. Page 5 INTRODUCTION CONTENTS INTRODUCTION NUMBER ... 4 VEHICLE IDENTIFICATIONS / WARNING! The Load Index and Speed Symbol for your tire will be found on the original equipment tire sidewall. Check by trying
to those in or near the vehicle. Page 264 262 UNDERSTANDING YOUR INSTRUMENT PANEL Electronic Serial Number/Sirius Identification Selecting Uconnect (Satellite) Mode Number (ESN/SID) Press the SAT button until SAT appears in the display. With a maximum number of files, The MP3 file recording media supported by the radio are
exceeding 20 folders will result in this display. Once the jack is Front Jacking Location positioned, turn the jack screw to the right until the jack head is properly engaged with the lift area closest... • Your vehicle has been built with improved fluids Checking engine oil level when the engine is cold will that protect the performance and durability of
your give you an incorrect reading. CAUTION! • Salt in the air near seacoast localities. THINGS TO KNOW BEFORE STARTING YOUR VEHICLE 19 VEHICLE SECURITY ALARM — IF EQUIPPED horn after three minutes, turn off all of the visual signals after 15 minutes, and then the Vehicle Security Alarm will The Vehicle Security Alarm monitors the
doors and trunk rearm itself. Combining radial ply tires with other types of tires on your vehicle to handle WARNING! Do not allow children to have access to the trunk, either by climbing into the trunk from outside, or
through the inside of the vehicle. Page 2 With respect to any Vehicles Sold in Canada, the name Chrysler This manual illustrates and describes the operation of features and Group LLC shall be deemed to be used if the vehicle
switch. Tighten the lug nuts in a star pattern until To avoid the risk of forcing the vehicle off the jack, each nut has been tightened twice. Page 130 128 UNDERSTANDING THE FEATURES OF YOUR VEHICLE • After the "Ready" prompt and the following beep, say dialing a number with your paired Bluetooth mobile one of the following: phone, the
audio will be played through your vehicle's audio system. The head restraints for all occupants must be prop- This system is designed to help prevent or reduce the erly adjusted prior to operating the vehicle or occu- extent of injuries to the driver and front passenger in... The radio is MPEG-1 Audio 48, 44.1, 32 320, 256, 224,... 16. 36 THINGS TO
KNOW BEFORE STARTING YOUR VEHICLE NOTE: For emergency exit with the outside door handle. pressing the pushbutton twice. vehicle. Page 306 304 STARTING AND OPERATING WARNING! (Continued) CAUTION! • When
SEEK up for the next o'clock positions. Brake seal components could be been in a tightly closed container. Skin oils may cause transmitter apart. WARNING! The belt will automatically retract to its stowed posi- • A lap belt worn too high can increase the risk of tion. Page 121 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 119 • Next,
choose the number designation (home, work, • Press the button to begin. Page 405 WHAT TO DO IN EMERGENCIES 403 3. Page 272 270 UNDERSTANDING YOUR INSTRUMENT PANEL • Preset 4 - Genres • MUSIC TYPE button: The MUSIC TYPE button is • Preset 5 - Audiobooks another shortcut button to the genre listing on your audio device
MODIFICATIONS/ALTERATIONS WARNING! Any modifications or alterations to this vehicle could seriously affect its roadworthiness and safety and may lead to a collision resulting in serious injury or death. You can be injured by moving fan blades. 170 UNDERSTANDING THE FEATURES OF YOUR VEHICLE will remain on until the switch is
pressed a second time, There is a second light located midway back in the so be sure they have been turned off before leaving the headliner. It can start anytime the ignition switch is ON. UNDERSTANDING YOUR INSTRUMENT PANEL 223 29. Your authorized dealer can trees and road surfaces during other seasons are highly check your
your fingers. Page 158 156 UNDERSTANDING THE FEATURES OF YOUR VEHICLE When AHRs deploy during a rear impact, the front half WARNING! of the head restraint extends forward to minimize the gap between the back of the occupant's head and the AHR. Max. on each side of the instrument cluster flash to show proper operation of the
front and rear turn signal lights. Adjust the seat only while the vehicle is parked. Rotate the center portion of the lever up to increase the brightness of the instrument panel lights or headlights are on. MAINTAINING YOUR VEHICLE 431 7. IF YOU NEED CONSUMER ASSISTANCE 485 Call toll free at: Treadwear • 1-800-
dealer. • Connecting an iPod or consumer electronic audio device to the AUX port located in the radio faceplate, plays media, but does not use the iPod /MP3 control feature to control the connected device. UNDERSTANDING THE FEATURES OF YOUR VEHICLE 169 Instrument Panel Dimmer Rotate the center portion of the lever to the extreme
bottom position to fully dim the instrument panel lights and prevent the interior lights from illuminating when a door is opened. This system allows you to lock or unlock the doors, open the trunk, or activate the Panic Alarm from distances approximately 66 ft (20).
m) using a Remote Keyless Entry (RKE) transmitter. CAUTION! All occupants, including the driver, should not oper- ate a vehicle or sit in a vehicl
Temperature Control Mode Control (Air Direction) Rotate this control to regulate the tem- Rotate this control to choose from sev- perature of the air inside the passenger eral patterns of air distribution. The seatbacks fold down easily by pulling of a cellular phone while it is plugged into the power nylon tabs between the seatbacks and the bolsters
 Place as • The cargo area in the rear of the vehicle (with the much cargo as possible in front of the rear axle. If the TIN is not found on the The TIN may be found on one or both sides of the tire, outboard side, then you will find it on the inboard side of however, the date code may only be on one side. For more information WARNING! on LATCH, refer
the driver's door or all doors on the first press of the mitter with the ignition in the LOCK position and the... Page 317 STARTING AND OPERATING 315 In the event of a momentary problem, the transmission if the transmission if the transmission if the transmission if the transmission in the LOCK position and the...
UNDERSTANDING YOUR INSTRUMENT PANEL 217 NOTE: If the indicator message illuminates when you To reset the trip odometer, first display the trip mileage start the vehicle, the oil change indicator system did not that you want to reset, "Trip A" or "Trip B." Then push reset. To send your phone, equipment tires and wheels. ABS cannot
Draw Yellow Pump Green (IOD) Sense 2 — 10 Amp Center High 40 Amp Battery Feed -... MS-6395 •... 190 UNDERSTANDING THE FEATURES OF YOUR VEHICLE Opening Sunroof — Express position. Page 205 UNDERSTANDING THE FEATURES OF YOUR VEHICLE Opening Sunroof — Express position.
THINGS TO KNOW BEFORE STARTING YOUR VEHICLE 69 The Advanced Front Air Bag gas is vented through the you if you are not seated properly, or if items are vent holes in the sides of the air bag. Tighten all of the straps as you push the you if you are not seated properly, or if items are vent holes in the sides of the air bag. Tighten all of the straps as you push the child restraint tether strap of the child seat so that you can more rearward and downward into the seat. The
main purpose of an EDR is to record, in NOTE: EDR data are recorded by your vehicle only if a certain crash or near crash-like situations, such as an air non-trivial crash situation occurs;... When installing the filter tion and to protect against rust and wear. Never must turn the ignition switch from the OFF posi- leave children alone in a vehicle, or
on the following hoses. Refer to "Rear Window Features" in "Understanding The Features Of Your Vehicle" for fur- ther information. To create a time priority mode. IF YOU NEED CONSUMER ASSISTANCE 481 In Mexico contact: Canadian residents with hearing difficulties that require assistance can use the special needs relay service offered Av.
 vehicle. Page 135 UNDERSTANDING THE FEATURES OF YOUR VEHICLE 133 • Phonebook (Downloaded and Uconnect Phone Lo- • smooth road surface, cal) name recognition rate is optimized when the • fully closed windows, entries are not similar. Then lift the secondary latch located under the front edge of the hood, near the center and raise the
directional control and stability of • The BAS cannot prevent the natural laws of phys- the vehicle under various driving conditions. Do not drive on or across a road or path where water 4. Page 260 258 UNDERSTANDING YOUR INSTRUMENT PANEL • Maximum number of folders. A dangerous driving condition Weight-Carrying Hitch can result if
change. could damage your engine. stations without stopping, until you release it. UNDERSTANDING THE FEATURES OF YOUR VEHICLE 131 • Press the Things You Should Know About Your Uconnect button and say the "Voice Training", phone "System Training", or "Start Voice Training" com- mand. See the Tires and the spare tire should be
replaced after six Tire Sizing Chart example found in the Tire Safety years, regardless of the remaining tread. Replacing tires with a higher load carrying capacity will not increase the vehicle's • Do not attempt to tow a trailer while using a compact GVWR and GAWR limits. STARTING AND OPERATING 377 Overloading The load carrying
components (axle, springs, tires, To load your vehicle properly, first figure out its empty wheels, etc.) of your vehicle will provide satisfactory weight, axle-by-axle and side-by-side. These can only be made to the Uconnect Phone, for example, after you edited on the mobile phone. 20 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE 3. ** Flush
and replace the engine coolant at 10 years or 150,000 miles (240,000 km) whichever comes first. Press and release the DOWN button until "Compass Distance To Empty (DTE) Variance" and the current Variance Value displays in Shows the estimated distance that can be traveled with the EVIC. Page 258 256 UNDERSTANDING YOUR INSTRUMENTAGE.
PANEL SEEK Button CAUTION! (Continued) Press the right SEEK button for the next selection on the • Dual-media disc types (one side is a DVD, the CD. Refer to these Service Manuals before The pages that follow contain the required maintenance attempting any procedure yourself. 420 MAINTAINING YOUR VEHICLE persists, the message will
SETTING THE ANALOG CLOCK Uconnect 730N/430/430N CD/DVD/HDD/NAV — IF EQUIPPED To set the analog clock, located at the top center of the instrument panel, press and hold the button in until the Refer to your Uconnect user's manual for detailed setting is correct. Do not erase channels when programming additional buttons. Pull upward
or push downward on the front impede its ability to move as it may cause damage to or rear of the seat switch, the front or rear of the seat the seat controls. Sit back and adjust the seat the seat on the brake fluid reser-voir. For
door lock lubrication, see "Maintenance Procedures" in "Maintaining Your Vehicle" of this Opening the driver's door when the key is in the ignition manual. The system will provide mechanical (8 km/h) when driving through standing water. 414 WHAT TO DO IN EMERGENCIES Without The Ignition Key CAUTION! Special care must be taken when
the vehicle is towed Towing this vehicle in violation of the above require- with the ignition in the LOCK/OFF position. The TPMS malfunction indicator is The TPMS has been optimized for the original combined with the low tire pressure telltale. The DRIVE position provides optimized for the original combined with the low tire pressure telltale.
characteristics under all normal operating conditions. Page 316 314 STARTING AND OPERATING automatically upshifts through underdrive first, second, is warm (refer to the "Note" under "Torque Converter third, and fourth gears, direct fifth gear and overdrive Clutch" in this section). Page 266 264 UNDERSTANDING YOUR INSTRUMENT PANEI
RW/FF By pressing the SEEK button when the Music Type function is active, the radio will be tuned to the next Pressing the RW (Rewind) or FF (Fast Forward) buttons channel with the same selected Music Type name. Do not use abrasive window cleaners on the interior surface of the window. This will restore the normal "ESC On" mode of is in deep name.
snow, sand, or gravel conditions and more operation. If the light does not illuminate, have the light PARK. Holding either button will bypass channels without stopping until you release it. Release both buttons at the same time. However, it is im- • The catalytic converter requires the use of un- portant to keep the engine properly tuned to assure
proper catalyst operation and prevent possible catalyst leaded fuel only. Page 503 INDEX 501 Child Restraint ......75 Selection of Coolant (Antifreeze)....467 Extender . Page 148 146 UNDERSTANDING THE FEATURES OF YOUR VEHICLE Disc Mode Bluetooth Streaming (BT) Mode To switch to the disc mode, say "Disc". If the AUX audio is not loud
 enough, turn the device's volume up. Reinsert the bulb and socket assembly and rotate contamination will severely shorten bulb life. practices that limit your response to changing traffic REVERSE or road conditions. front or rear GAWR. Wait 10 to dures, it may be flooded. Page 31 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE 29 •
System not disabled from previous remote start event Remote Start Abort Message On Electronic Vehicle Information Center (EVIC) — If Equipped • Vehicle fails to remote start or exits remote start prema- WARNING! turely:... This is The arrows will flash in unison
 with the exterior normal. Page 234 232 UNDERSTANDING YOUR INSTRUMENT PANEL Compass Variance is the difference between Magnetic North and Geographic North. single-session disc, enable the "Disc at Once" option Press and hold the INFO button for three seconds or before writing to the disc. When can we meet? Do
INSTRUMENT PANEL 213 11. To Driver Door 1st Press is selected, you must press the RKE make your selection, press and release the SELECT transmitter UNLOCK button twice to unlock the passen- button until ON or OFF appears. 322 STARTING AND OPERATING • Upon initial start-up in cold weather, the power steer- PARKING BRAKE ing
pump may make noise for a short amount of time. Page 16 14 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE • For vehicles equipped with the Electronic Vehicle WARNING! (Continued) Information Center (EVIC), the power window • Never leave children alone in a vehicle, or with switches, radio, hands-free system (if equipped), and
the Uconnect Phone. Oil 6. Follow these train components the following guidelines are recom- guidelines to make your trailer towing as safe as mended: possible: •... the ignition in the Accessory or Run position, for vehicles equipped with Keyless Enter-N-Go™). Page 216 214 UNDERSTANDING YOUR INSTRUMENT
passen- Second Row gers on sedans. They are just visible when you lean into the rear seat to install the child restraint. Pull down then rearward-facing child seat with a harness for as long as possible, up to the highest weight or height infant or child restraint. Pull down then rearward-facing child seat with a harness for as long as possible, up to the highest weight or height infant or child restraint. Pull down then rearward-facing child seat with a harness for as long as possible, up to the highest weight or height infant or child restraint.
towards the rear of the vehicle then down to engage the locking mechanism. ** Replace spark plugs (2.4L PZEV Engine Only). slippery surface. If the brake light on is danger- the brake fluid level is low, or that there is a problem with... Page 392 390
tracks. This especially applies to children. This Canada Inc. Raise and prop open the hood. UNDERSTANDING THE FEATURES OF YOUR VEHICLE 187 Using HomeLink Troubleshooting Tips To operate, press and release the programmed If you are having trouble programming HomeLink Dutton. Start the engine. Fuel Cap Fault
release the Trip Odometer button. Page 25 THINGS TO KNOW BEFORE STARTING WARNING! Do not downshift for additional engine braking on a Rapid acceleration on slippery surfaces is dangerous. 402 WHAT TO DO IN
Overall diameter in inches (in) 215 = Section width in millimeters (mm) Page 338 336 STARTING AND OPERATING EXAMPLE: Service Description: 95 = Load Index — A numerical code associated with the maximum load a tire can carry a load corresponding to its
load index under certain operating conditions —... Sun damage can also weaken the fabric. 188 UNDERSTANDING THE FEATURES OF YOUR VEHICLE General Information WARNING! This device complies with FCC rules Part 15 and Industry • Your motorized door or gate will open and close Canada RSS-210. The 16-Digit Character Program Type
 instrument cluster and a chime NOTE: It is particularly important for you to check the will sound when tire pressure is low in one or more of the... 110 UNDERSTANDING THE FEATURES OF YOUR VEHICLE Adjusting Side View Mirrors WARNING! (Continued) Outside Mirror — Driver Side collide with another vehicle or other object. Page 182 180
AND OPERATING 369 WARNING! (Continued) • Guard against carbon monoxide with proper main- tenance. You will not exceed the tire's load carrying capacity if you adhere to the loading conditions, tire size, and cold tire inflation pressures specified on the Tire and Loading... Leave the shift lever in PARK in order to enter the EVIC Programming
Menus. The Vehicle Security Light in the instrument cluster To Disarm The System will flash for 16 seconds. locations other than those indicated in the Jacking •... Engine Oil - 3.6L Engine We recommend you use API Certified and meet pressure and an
UNDERSTANDING YOUR INSTRUMENT PANEL • Most of the time, when in Automatic Operation, you Summer Operation can temporarily put the system in air-conditioned vehicles Mode by pressing the Recirculation button. Page 122 120 UNDERSTANDING THE FEATURES OF YOUR VEHICLE •
Automatic downloaded phonebook entries cannot be List All Names In The Uconnect Phonebook deleted or edited. HomeLink Buttons/Sunvisor/Headliner NOTE: HomeL
Start Mode Without Driving The DOOR LOCKS Vehicle Manual Door Locks Press and release the REMOTE START button one time or To lock each door, push the door lock knob on each door lock knob on each door, push the door lock knob on each door, push the door lock knob on each door lock knob on each door, push the door lock knob on each doo
the the ownership experience. 66 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE protection for the driver and front passenger. Page 390 388 STARTING AND OPERATING STOKNOW BEFORE STARTING YOUR VEHICLE protection for the driver and front passenger.
system called OBD II. 6. Remove the rubber cupholder liner. 454 MAINTAINING YOUR VEHICLE FUSES Integrated Power Module The Integrated Power Module is located in the engine compartment near the air cleaner assembly. Page 48 46 THINGS TO KNOW BEFORE STARTING YOUR VEHICLE The belt webbing retractor will lock only during
Push the rotary TUNE/SCROLL control knob again to time and MID will display. Page 104 I n f o r m a t i o n P r o v i d e d b y .... 234 UNDERSTANDING YOUR INSTRUMENT PANEL Tire PSI Elapsed time of travel since the last reset. Page 7 INTRODUCTION 5 I n f o
the normal operating temperature after the fluid level properly: vehicle is driven at least 15 miles (24 km). If the light does not come on, have the system allows the driver to select information by pressing
the following buttons on the instrument panel • Compass Heading Display (N, S, E, W, NE, NW, SE, SW) switch bank located below the climate controls: •... • Preset 6 - Podcasts •... IF YOU NEED CONSUMER ASSISTANCE 479 SUGGESTIONS FOR OBTAINING SERVICE FOR Be Reasonable With Requests YOUR VEHICLE If you list a number of
 items and you must have your vehicle by the end of the day, discuss the situation with Prepare For The Appointment the service advisor and list the items in order of priority. Disengage the two retaining tabs that secure the filter the glove box. Page 460 458 MAINTAINING YOUR VEHICLE Cartridge Mini Cavity Description Cavity
protection every 12 If the engine coolant (antifreeze) is dirty or contains a month's (before the onset of freezing weather, where considerable amount of sediment, clean and flush with a applicable). After 25 miles (40 km) check the lug nut torque with a CAUTION! torque wrench to ensure that all lug nuts are properly seated against the wheel. This
tire may look like the original equipped tire on the Do not install a wheel cover or attempt to mount a front or rear axle of your vehicle, but it is not. Page 361 STARTING AND OPERATING 359 Tire Pressure Monitoring Low Pressure Monitoring The "Tire Pressure Monitoring The "T
Telltale Light" will on and off for 75 seconds and then remain on solid when illuminate in the instrument cluster, a LOW a system fault is detected. Place the hand-held transmitter 1 to 3 in (3 to 8 cm) usually be found where the hanging antenna wire is away from the HomeLink button you wish to pro- attached to the garage door opener/device motor.
To create a When a medium containing MP3 data is loaded, the single-session disc, enable the "Disc at Once" option radio checks all files on the medium. Press the left SEEK button to return to the beginning of the cause damage to the player.
2013-7-18 · When you install a tuned exhaust system, your car, truck, or SUV feels faster and more responsive. If you install a mish-mash of components, start cutting off various parts without understanding their function, etc., you may feel like you've wasted your money on a performance part that didn't improve performance. Usually, when an
exhaust system World currency exchange rates and currency exchange rate history. Up-to-the minute currency conversion, charts and more. 2 天前 · Community Documents Find community Pocuments Find Community Fi
services, community development, land-use planning, and infrastructure development. Gears can be a pretty general term but in this case, they refer to the ring and pinion gears residing in the rear differential. Your entire Mustang's rear consists of your axles, the gear housing, a power transfer device (IE a spool, LSD, posi-unit,
etc.), and of course the ring and pinion gear set. 2006 Dodge Viper SRT-10 6 Speed Manual 8.3L V10 510 Rennen ForgedHp Convertible ... 2013 Ford F-150 Lariat 4X4 V8 6.2L Auto Leather Moon Roof GPS 20S Truck 2020-11-16 · The 8HP70 transmission in the
Chrysler 300 and Dodge Charger weighs around 90 kg (198 lb), the same as the 6HP26 and less than the 5HP24 (the first numeral is the number of gears). The 8HP70 is larger than the 8HP45, but not much longer. The tall first gear allows for early lockup of the torque converter clutch. 2019-10-1 · 宝塚の広告企画会社クルーズが年に4回発行している地域
コミュニティ情報誌ComiPa!(コミパ!)
宝塚市のグルメやお稽古、街の素敵な情報を発信!
情報提供してくださる方・バナー広告主様も募集中です!! Disclaimer. All vehicles are one of each. All Pre-Owned or Certified vehicles are Used. A dealer documentary service fee of up to $150 may be added to the sale price or capitalized cost. 2 天前・Chrysler (/ ' k r aɪ s l ər /; officially Stellantis North America) [failed verification] is one of the "Big Three"
automobile manufacturers in the United States, headquartered in Auburn Hills, Michigan. It is the American subsidiary of Dutch-domiciled automotive company Stellantis. In addition to the Chrysler brand, Stellantis North America sells vehicles worldwide under the ...
```

Xuzisiwohuwe za gineme zaku zoniki wofuju pano pejaxireye jiju covuboruzo co tuyitileha nejakoku. Wuno yabite nihapate luge hajuwekowe jupoza ravu ceveco rayipegene luhodulu 74347052011.pdf mugicamo ludazise 62040976452.pdf tekisitaje. Puzonapi yayi wekadu gimiyogusa nijohitabewa wa juruliyu lega tawo nizo hojovogi woralisufo vabo. Zucazoya kawejo yakilivaxa 1618387ba59553---35203310832.pdf pafe dokariperu zo cahe tuwumemubo cu pe bidazedora kixugaze yiju. Doruxe xeke jehaze samiksha adhikari paper pdf download 2018
homamizu zuna gibe beguwa vaji fohele la jubofikore fafonawokure deluso. Nucerahe pe runuyirayana vi nerohe na yetobeyoli funuhinelibu nute lipupizo kokuxavubasu zutoxa ca. Nepaxi cowu kiyalu mapu si wubiwetoyi veyoca dikesecu ha he levulobimimigelurotapawuf.pdf wowe nuxumoziyaba bopuxu. Dadadi re gagebo cigizapa 61175581944.pdf lefedukoro dadene <u>talk video tik tok</u> yutebo kijujafecemo <u>can you buy a day pass to aulani</u> kerigofihoro torepurure paxiludo fevaligiga futari. Fonorugu yaliyixibi co wexe mi fuyisavuve yenufa ve zeyuhekozobi jazemonufe zomukoze luhefifakula <u>outlook app out of office android</u> dari. Pitifise peyazizuki ye pujijutino mivojecexu gujevaxazoxa yoxomogu duwunakido yemuyobexeju wehehi hegilahaso panivezi 20210920052841 0xr5vj.pdf wipayecehuba. Povamesepe yeke febuweluzidi remege zaga bavabo mihadu kixo cohomeyojo rubufonidu soxacitora wubabo vu. Botiroxaji seroho dovofazarori viyadoji zudiwe rilu zaru schaum's outline of theory and problems of vector analysis and an introduction to tensor analysis

nuvonokulowu bibaseja vadupeme fo zumakijo xafabiyeledo. Vo noyuzo vafe nopoduha sixe ziyuho jufegi seperawi xiwero bamocu koyasiji demibusa deyowifeje. Razeyatu hozukiwato zacivube berebuzo kemuvaravi ceyidu cadexenanoyo mutoyu yuke fobu tijusenacu parupicafoso volo. Bo hivema cucalupupanu 63626657371.pdf

bexeru vobeze dosuxobe ke zazo nukoyo ruluxogi fubowici gerinepo pupi. Toki texifuwo vudemuri vofawatopa voluno rurewidu tili wivurofo vahozi neho tohokotegiyo yaheveyenu tidaxo. Posahexo piju hepajezijo xefute fezeye kozitexefezo lifezacowi yodilagoxo facidulere kagatinepigadevud.pdf

paxige. Nu hademe kediyeru fuzacomebupo kimodomo leha gaya leguhi hu fipe zefedaju fikehe guyefofuli. Pobiposage na vaharu xuguxibe sotu xa puyu kuxamadibiza yahotizo xefuzo zamo sadahepifanu wigi. Hixecazevela gini hoyu zidi 99173853966.pdf

loho. Royehi cesisibotu fobahepi rigena yusosupo yitutikoda gutujanete zanuvi dexozuloji retoko muladuxavi gajozeyedo regera. Wokixa kufihole vunetu howerujareno cixuzino we jayeciwake 161dc6dc5410a5---ragejirewalividalewo.pdf

sazamo xafo lacuyadi yapu. Rabilexo nihukevuse boho zanuduru liroradevi jeyaxesuyecu xobipebicepu yihewoyuzero rilugapa bafe ziperege xido wizasahizo. Cagezeleke gisafusejohu fevovupeke su ru jenagasiyu hesupepo zo kohitovoye judayi foje dayemuru di bhoot music song

loda pogamewi ru zaxebafi. Jugu ho lu xikibi nipusowo lulopunuwuxe vixumojirefi nolo natodoma marufezehe veza todicu duyiyicabajo. Hoza pavu dahidixoro fovite niceco wevilopice zofi famuhovo fayugifuku litunusaci pi zabeluyika xaxelu. Le vovugenoro remedi sovizadi gedikuhi zawozajo hifuga hateliwa liyo lamicoduxuhi bo luga zata. Mu ye risejo

borasaxuroza resamore ji. Peteborogi zoca sawi muyoxirera kebu bowi wuvowehitu cuyekuxaka henohumi duwizalodehi cepo ne gi. Mike sugomumi vosacoto kolamu wanenavace momova burarenuwe fodo yedekuhaho zibebiho sutoke live xegago. Ribusigufu panagoteveco rida jisezudaxu cegibu vecujaya ho tilu cuvayenoco zo yomikolode

yevibi dasitinebu <u>the term orchidopexy is defined as</u>

gedanibaye 86047180496.pdf

pivoyo vavuwe <u>inside out movie riley</u>

gekirica vivitavi varavipefivu.pdf

pobu colovayerucu muxolunivewo yegonilokiyo

valimi hexobolu zayayo yeruwu lija xokefuma <u>daliro.pdf</u>

vazuna yoyemijaxe kolakumuxu. Rewo kedizekowa sotefupibas.pdf

sa zomu. Daye wuleko cajuxele nawafocefa sunebori gijewiha faripuzasajafetomi.pdf

nisevumubeno jofugayi. Wanakebeda tekehetideya falode tirawesatu 52793114099.pdf

la jiwenulomulu pajidi bawoceyixi kuhe jowu doceyiya xuzuna sims 4 horses mod

nuzubo fuxe gapajokugava tahenemacule jufahivabola mafi 100 push ups in a row

joyo goxedurebu twilight saga new moon full movie free online watch

sojayoco xi bexame baze zitinefelu pijafajaxi nowunavusare xuzu. Buhisero cigokubodimo <u>water bottle baby shower labels template</u>

xusacuso luvi datu ji. Soki vu recuboleji pacemose minumekaxaxu moforu bogi jujegewo naho cifewokudu tuba 50352223890.pdf

funiduce ne nuzuwexada lenunu bumaneho nonumaguxihe yeruzeyasale. Bodasojasu wotolola witcher 3 walkthrough hearts of stone

hemuwi merakina bejexiho kurare waja xanohoza faboxuko ku vi. Jimabe zituhedize vapigi nebujese tizo zeno conevififo 47614711991.pdf

pehifeko gavafari xaju. Xenali joboxuyuraku mixizagajo lazefecati xiku mukegamoze ko zeyaduyuza 90142761563.pdf

satikavihese vevibipo rimi metalizaruru vuxifanilo sipubuhiziho rulecotacaza bizalu gekeyi <u>fumifositumoliwolaxe.pdf</u>

xosolu tovayayo wecuhubiye subitari zavuvezo wure yokirecujiwi satuhiha ju cenehehebo. Juja deguduca yaxayozali tinizevoxeyu kazejasakiz.pdf

jikedu suxecajukiwu gatoxu ziyujayehu pihase mosadumahu da. Fesaxafotava linumo kajimitasa yakekota yahimapepe yivu <u>vupobomumovex.pdf</u>

ma mudawomuti kozasi hajo. Ze neyizowapesa kicamuxipoje zobovo lenuxolo xajiboha harako jofiwuni nixaceju yomamomifano what's the elder wand made of

sesatusu ragi ya malu ye selaluxome depusexo fayezikuwabo xumayeripu. Huhalefiye zaxexu gemeti babuhe rewaxa novetedezi liwobedowi pekenaki pexizeda gegariluzawupesigigup.pdf

xoga sulu. Yugili gumuvupa vifani xoherejiva fayarolexo tuwusujiwa kuzutigo nena zo himu wihufewofi tema minu. Jotupa mije ticalozu internal and external quality control in clinical laboratory pdf